



701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com

HOBART DISPOSER SELECTOR CHART

FOOD WASTE DISPOSERS – A SIZE TO SOLVE ANY FOOD WASTE PROBLEM

A disposer installed at each work station, in addition to the soiled dish table unit, provides the maximum of convenience and sanitation. Food waste is ground and flushed through the drain lines instead of accumulating... eliminates handling and storage of filled garbage containers.

The Selector Chart is based on disposing of average food waste mix. ½ lb. food waste/person/meal should be used as a guide. If the mix will include a large percentage of bones or other hard materials, specify a larger model disposer or additional units.

Refer to Hobart Food Waste Disposer specification sheets for wide selection of accessories and controls.

HOBART DISPOSER SELECTOR CHART

MEALS PER DAY		200 to 300	300 to 500	500 to 1,000	1,000 to 2,000	2,000 to 4,000
RESTAURANT HOTEL HOSPITAL	Soiled Dish Table	FD4/125	FD4/150	FD4/200	FD4/300	FD4/500
CAFETERIA COMMISSARY SCHOOL	Soiled Dish Table	FD4/75	FD4/125	FD4/150	FD4/200	FD4/300
POINT OF ORIGIN	Vegetable – Salad Prep Area	FD4/75	FD4/125	FD4/125	FD4/150	FD4/200
	Scullery Area	FD4/50	FD4/75	FD4/75	FD4/75	FD4/125

Complies with
ASSE 1009



FD4/50 (½ H.P.)
FD4/75 (¾ H.P.)
FD4/125 (1¼ H.P.)



FD4/150 (1½ H.P.)
FD4/200 (2 H.P.)
FD4/300 (3 H.P.)



FD4/500 (5 H.P.)

HOBART DISPOSER SELECTOR CHART



701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com

SPECIFICATIONS

DUAL DIRECTIONAL GRINDING: Automatic reversing of disposer's direction of rotation when installed with Control Group 5 or 6. Increases life and efficiency of grinding elements by dispersing the wear factor. Will reverse unit, freeing it up in case a jamming situation occurs.

CONES: All models FD4/50 through FD4/500 fit the same large 7" throat opening diameter. Cones of hydroformed stainless steel, 18" bowl diameter is standard; 15" is optional. Both feature a dual directional water inlet for flushing waste into the disposer.

VINYL ISOLATING RING: Eliminates metal to metal contact and prevents vibration and noise transmission. Sink and trough mounting accessories are also available.

ADAPTERS: Are available to install Hobart Disposers on existing Cones (See Form F7543).

THERE IS NO SUBSTITUTE FOR SUPERIOR
DESIGN, QUALITY AND RUGGED CONSTRUCTION

As continued product improvement is a policy of Hobart, specifications are subject to change without notice.