



BEVERAGE-AIR

BLAST CHILLER/FREEZERS

MODEL WIDTH	MODEL #	VOLTS	AMPS	CUBIC FEET	WIDTH	DEPTH	HEIGHT	CRATED WEIGHT	PAN CAPACITY	CHILLING CYCLE	CHILLING CAPACITY
22"	CF031AG	115-120	9.9	7.3	22.05	27.6	20.47	104	3	194° to 37° F (90 minutes)	17.6 lbs
										194° to 0° F (240 minutes)	11 lbs

Depth measurement includes handles.
Height measurement includes mounting height.

BLAST CHILLER/FREEZERS

MODEL WIDTH	MODEL #	VOLTS	AMPS	CUBIC FEET	WIDTH	DEPTH	HEIGHT	CRATED WEIGHT	PAN CAPACITY	CHILLING CYCLE	CHILLING CAPACITY
31"	BF051AG	230	6.7	13.9	31.1	27.56	33	304	5	194° to 37° F (90 minutes)	40 lbs
										194° to 0° F (240 minutes)	26 lbs

Self-closing doors
with still position at 100 degrees

Ergonomic handles

6" casters standard

Depth measurement includes handles.
Height measurement includes mounting height.

WILLIAMS BLAST CHILLERS

MODEL WIDTH	MODEL #	DOORS/ SHELVES	VOLTS	HP	AMPS	CUBIC FEET	WIDTH	DEPTH	HEIGHT	CRATED WEIGHT	CHILLING CYCLE	CHILLING CAPACITY
28"	WBC35	1/5	208-230	3/4	7	35	28	32	35	275	160° to 38° F (90 minutes)	35 lbs
35.5"	WBC75	1/12	208	1 1/2	15	75	35.5	36	77.5	595	160° to 38° F (90 minutes)	75 lbs
43"	WBC110	1/12	208-230	1 1/2	8.6	110	43.38	40.63	81	747	160° to 38° F (90 minutes)	110 lbs

Depth measurement includes handles.
Height measurement includes mounting height.



BA8C4P20190719



888-845-9800
beverage-air.com

3779 CHAMPION BLVD.
WINSTON-SALEM, NC 27105
PHONE: (888) 845-9800 | FAX: (800) 253-5168
EMAIL: SALES@BEVAIR.COM
WEB: BEVERAGE-AIR.COM



an Ali Group Company



The Spirit of Excellence

BLAST CHILLERS/FREEZERS

BEVERAGE-AIR BLAST CHILLERS/FREEZERS

- Compact construction
- Electronic control board display
- Custom chill/freeze cycles
- Core temperature probe
- Manual defrost
- Insulation is CFC and HCFC free, high density polyurethane
- R404A refrigeration
- Self-contained refrigeration



3 YEAR PARTS AND LABOR / ADDITONAL 2 YEAR COMPRESSOR PART WARRANTY
AUTOMATIC PRODUCT STORING AT END OF CYCLE
UP TO 99 CUSTOM PROGRAMMABLE CYCLES



CORE PROBE
measures product temperature



ELECTRONIC CONTROL DISPLAY
intuitive programmable display

EXTERIOR FINISHES

- Stainless steel

INTERIOR FINISHES

- Stainless steel

AGENCY CERTIFICATIONS



WILLIAMS BLAST CHILLERS

Polished stainless steel front, sides, and door maintain an attractive appearance after years of heavy use

Stainless steel interior

Self-closing door

Easy-to-replace balloon gasket prevents cold air from escaping

Door heater to prevent condensation from forming on the cabinet front

Unique 1-2-3 microprocessor control panel initiates blast cycles in three simple steps

Built-in alarms

Temperature probes or a digital timer can control the chilling process

Programmable with two preset chilling times for specific food products



DOOR HEATER IS PROVIDED AS STANDARD TO PREVENT CONDENSATION FROM FORMING ON THE CABINET FRONT
STAINLESS STEEL EXTERIOR AND INTERIOR TO MAINTAIN AN ATTRACTIVE APPEARANCE AFTER YEARS OF HEAVY USE



FRONT BREATHING
on reach-in and undercounter models



1-2-3 MICROPROCESSOR
control panel

AVAILABLE DOORS

- Solid

EXTERIOR FINISHES

- Stainless steel

INTERIOR FINISHES

- Stainless steel

AGENCY CERTIFICATIONS



BEVERAGE-AIR

888-845-9800 beverage-air.com