

APak® Alarm Systems

91104-0001 Apak® Outdoor Alarm

SPECIFICATIONS:

- APak Outdoor Alarm System Features
- NEMA 4X Outdoor use per UL 864 for US and Canada
- Alarm system (horn & light) operates to warn of a high-water condition
- Horn is rated 82 decibels at 10' (3 m)
- Auxiliary dry contacts for high level alarm, 5 Amps
- Operates on separate circuit from pump, 115 VAC
- Alarm test and horn silence switch with automatic reset
- Terminal connections for a pump and float switch (Model 91104-0001)
- Can be used with liquids to 140 °F (60 °C)
- 15' (5 m) float switch (Model 91104-0001)
- 20' (6 m) float switch, 6' (2 m) power cord, watertight cord connectors (Model 10-0682)
- 3 year limited warranty (Model 10-2614, 10-0682, 91104-0001)

NOTE: All variable level float switches in this section are mechanically activated and do not contain mercury.



ACCESSORIES AND CONTROLS

91104-0002 Apak® Outdoor Alarm

SPECIFICATIONS:

Same standard features of our 91104-0001 with:

- 20' (6 m) alarm (12 V) tethered switch
- 6' (2 m), 115 V power cord with water-tight cord connectors

Flood Alert®

10-0763 High Water Alarm

SPECIFICATIONS:

- Operates on (3) AAA batteries
- Low battery alarm
- Warns you when sensor contacts water
- Loud intermittent horn rated at 103 +/- 3 db at 1' (30 cm)
- On/Off silence switch
- Stainless steel sensor contacts
- Easy to install, portable and safe!
- Compact design (3-1/4" x 2-1/4" [8.3 x 5.7 cm])
- No adjustments needed
- Solid state electronic components
- 5' (1.5 m) of lead wire
- 12-month limited warranty
- AC power adapter capability. Requires Class 2 transformer, Input: 120 VAC/60 Hz, output: 4.5 VDC/150 mA, tip positive, type B plug. (Not included, but available at most electronics stores)

Flexible sensor wire allows this alert to be used in many applications. Alerts you of overflowing:

- Sump pump • Toilets • Broken pipes
- Dishwashers or washing machines • Laundry sinks
- Air conditioning pans • Bath tubs or hot tubs

