



ABS-9KD-30H

30-Gallon

Industrial Two Stage – Diesel

This two stage diesel-powered air compressor provides consistent and reliable air power for industrial, automotive and service body applications.

Compressor Pump

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Engine

- Electric start - battery, box and cables not included
- Glow plug equipped for easy starting in cold temperatures

Frame

- Powder coated ASME receiver tank
- $\frac{3}{16}$ -inch base plate to reduce vibration
- Powder coated two-piece belt guard
- Removable base plate offers flexible installation

Components

- Regulator and two gauges for tank and outlet pressure
- ASME safety valves
- Tank drain valve

Limited Warranties

- 2 year pump exchange (*see page 87*)
- 3 year Kohler engine

Certification

- ASME Boiler and Pressure Vessel Code - UM

MODEL NUMBER	CFM @ PSI*	HORSEPOWER/ENGINE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-9KD-30H	29.0 @ 175	9.1 HP Kohler KD440 OHV	Cable throttle	38x23x46.5in.	540 lb.	483 lb.

*Equipped with 150-PSI maximum rated regulator.

ACCESSORIES AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODEL	PART NUMBER	DESCRIPTION	FITS MODEL
AW-6000-1002	Equipment cover	ABS-9KD-30H	IX-0001	Vibration isolator pads – Recommended for models mounted in service truck applications	ABS-9KD-30H
AX-0079	Battery box, cables and tray	ABS-9KD-30H			

5-Gallon

Industrial Single Stage – Electric

This 5-gallon, hand-carry air compressor is perfect for small, interior jobs where space is limited and portability is essential.



NEMA 5-15P,
15-amp plug



AM1-HE02-05M

Compressor Pump

- Cast iron compressor pump
- Splash lubricated aluminum crankcase
- Stainless-steel braided discharge hose
- Inlet air filter

Motor

- Thermal overload motor protection
- 8-foot power cord

Frame

- Powder coated twin tank assembly
- Protective pump/motor housing

Components

- Regulator and two gauges for tank and outlet pressure
- Drain and pressure relief valves
- Industrial interchange quick connect fittings
- Start/stop control set at 95 to 125-PSI

Limited Warranties

- 1 year compressor pump
- 1 year electric motor

Certification

- ETL Certified - US and Canada

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-HE02-05M	4.2 @ 90	2.0 HP, 120V, 15.0A	NEMA 5-15P	20.5x15.5x17.5in.	70 lb.	61 lb.