

TEMPORARY ANCHORAGE CONNECTORS

Anchorage Connectors are designed as the intermediary for securing a connecting device to an anchorage. Careful consideration should be given to selecting a proper anchorage for ultimate safety. The anchorage should be easily accessible, located a safe distance above any lower obstacles, and support 5,000 lb per worker.

CROSS-ARM ANCHORAGE CONNECTORS

Explore our selection of Cross-Arm Anchorage Connectors, designed to provide reliable support and stability for a variety of structural applications. 400 lb maximum capacity.

SKU	Description	Material
8180/22INGN	Scaffold short choker 22 in	Nylon
8183/2FTGN	2 ft model	Nylon
8183/3FTGN	3 ft model	Nylon
8183/4FTGN	4 ft model	Nylon
8183/5FTGN	5 ft model	Nylon
8183/6FTGN	6 ft model	Nylon
8183/8FTGN	8 ft model	Nylon
8183/12FTGN	12 ft model	Nylon
8183/15FTGN	15 ft model	Nylon
8183/20FTGN	20 ft model	Nylon
8183/25FTGN	25 ft model	Nylon
8184/3FTGN	3 ft model with wear pad	Nylon
8184/6FTGN	6 ft model with wear pad	Nylon
8185/2FTGN	2 ft model	Nylon
8185/3FTGN	3 ft model	Nylon
8185/4FTGN	4 ft model	Nylon
8185/5FTGN	5 ft model	Nylon
8185/6FTGN	6 ft model	Nylon
T7314/3FTAF	Titan 3 ft model	Polyester
T7314/4FTAF	Titan 4 ft model	Polyester
T7314/6FTAF	Titan 6 ft model	Polyester
8185K/2FTBK	2 ft model	Kevlar
8185K/3FTBK	3 ft model	Kevlar
8185K/6FTBL	6 ft model	Kevlar



8180/22INGN



8183/3FTGN



8185/6FTGN



440/6FT

CROSS-ARM CHAIN ANCHOR

The 6 ft chain anchor provides a single user with an easy-to-install, temporary anchorage connector. It easily wraps around I-beams or other structures. This product safely wraps around corners and sharp edges and is ideal to use in environments where chemical, heat, or welding splatter may occur. 400 lb maximum capacity.

SKU	Description
440/6FT	6 ft model