

COXREELS® SS Series "Stainless Steel" spring driven hose reels have similar features to their related series, but are constructed of high quality electro-polished stainless steel with stainless steel fluid paths. They offer clean, non-corrosive performance in applications that require it, such as food and chemical processing, marinas, and anywhere that rust, corrosion and contamination thrive.

SS SERIES

LESS HOSE						SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	
P SERIES						
P-LPL-335-SS	3⁄8"	1⁄2"	35	300	34	1
P-LPL-350-SS	3⁄8"	5⁄8"	50	300	39	1
P-LPL-425-SS	1⁄2"	3⁄4"	25	300	39	2
SH & MP SERIES						
SHL-N-350-SS	3⁄8"	5⁄8"	50	300	44	3
SHL-N-450-SS	1⁄2"	3⁄4"	50	300	46	3
SHL-N-525-SS	3⁄4"	1 1⁄16"	25	300	45	4
MPL-N-350-SS	3⁄8"	1 1⁄16"	50	3,000	53	3
MPL-N-450-SS	1⁄2"	1 3⁄16"	50	2,500	53	3
T SERIES						
TSHL-N-350-SS	3⁄8"	5⁄8"	50	300	55	5
TSHL-N-375-SS	3⁄8"	5⁄8"	75	300	73	6
TSHL-N-3100-SS	3⁄8"	5⁄8"	100	300	74	6
TSHL-N-450-SS	1⁄2"	3⁄4"	50	300	55	5
TSHL-N-475-SS	1⁄2"	3⁄4"	75	300	71	6
TSHL-N-4100-SS	1⁄2"	3⁄4"	100	300	80	6
TSHL-N-550-SS	3⁄4"	1 1⁄16"	50	300	70	7
TMPL-N-3100-SS	3⁄8"	1 1⁄16"	100	3,000	82	6
TMPL-N-4100-SS	1⁄2"	1 3⁄16"	100	3,000	80	6
EN SERIES						
ENL-N-335-SS	3⁄8"	5⁄8"	35	300	46	8
ENL-N-350-SS	3⁄8"	5⁄8"	50	300	58	9
ENL-N-425-SS	1⁄2"	3⁄4"	25	300	63	8
ENL-N-450-SS	1⁄2"	3⁄4"	50	300	61	9
ENML-N-335-SS	3⁄8"	1 1⁄16"	35	3,000	64	8
ENML-N-350-SS	3⁄8"	1 1⁄16"	50	3,000	80	9
ENML-N-425-SS	1⁄2"	1 3⁄16"	25	2,500	61	8
ENML-N-450-SS	1⁄2"	1 3⁄16"	50	2,500	82	9

REEL DIMENSIONS

Technical Data Sheets Available On Website


SIZE INDEX	W	H	L	X	Y	M	N
1	6 3/4"	18 5/8"	17 1/8"	6"	6"	4"	5"
2	7"	18 5/8"	17 1/8"	6"	6"	4"	5"
3	8 1/4"	21 1/4"	19 1/2"	6"	6"	4"	5"
4	9 3/8"	21 1/4"	19 1/2"	6"	6"	4"	5"
5	9 3/8"	21 1/4"	19 1/2"	8"	9"	7"	8"
6	9 3/8"	25 1/2"	24"	8"	9"	7"	8"
7	9 7/8"	25 1/2"	24"	8"	9"	7"	8"
8	6 7/8"	18 7/8"	19"	6"	6"	4"	5"
9	8 1/2"	21 3/4"	21 7/8"	6"	6"	4"	5"

Overall Dimensions


Base

Mounting Pattern


P Series



T Series



EN Series



SS-P Series



SS-T Series

SS SERIES - SPRING :: REEL SPECIFICATIONS

SWIVEL

- Non-corrosive external fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE Non-Toxic Food Grade Grease

DESIGN & STRUCTURE

- Electro-polished stainless steel finish
- Each of these reels is built of their standard series with their own unique features & benefits

RETRACTION

- Enclosed factory tuned & matched cartridge-style spring motor
- Non corrosive stainless steel spring, pawl & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Corrosive Environments
- Hygienic Environments
- Medical Services
- Marine/Docks/Offshore
- Manufacturing Plants & Facilities
- Pulp & Paper Plants
- Food & Chemical Processing Plants
- Bottling Plants
- Dairies
- Meat Packing
- Grocery Stores
- Restaurants & Commercial Kitchens
- Water Treatment & Supply
- Petrochemical
- Food Grade Washdown

ACCESSORIZE YOUR REEL :: PG 56

- O-Rings & Swivels
- Mounting Brackets
- Hoses
- Assorted Reel Accessories



WARNING: Cancer and reproductive Harm – See page 63 for more information – www.P65Warning.ca.gov