

Electronic Exposed Solar TECK® Flush Valves

TECK®
COMMERCIAL



81T201SP-MMO

Exposed Solar Flush Valve 1-1/2" Top Inlet Closet Fixture

- Polished chrome-plated vandal resistant metal cover with top mounted electronic sensor and solar module
- True mechanical manual override button (MMO)**
- Right or left-hand supply installation
- ADA compliant, automatic operation with infrared sensor
- Designed for indoor lighting conditions and will operate in high or low brightness levels
- Compatible in environments with occupancy lighting
- Scratch resistant lens window
- Four (4) size AA alkaline batteries factory installed (required and included) with valve in shipping mode for easy installation
- Battery strength indicator with low battery warning light
- Supplied with an advanced infrared sensor activated flush system that uses multiple detection distances along with a bowl length setting to react appropriately to different usage patterns
- Optional 24 hour automatic flush factory set to OFF
- Set-up sensor range adjustment indicator lights
- 6 second arming delay
- TECK® exposed diaphragm flush valve
- Chloramine resistant diaphragm
- Renewable seat
- Polished chrome-plated body
- External water conserving flush adjustment**, factory set to 6 Lpf (1.6 gpf)
- 1" FIP/Copper sweat inlet adaptor**, angle check stop with protecting cap
- Adjustable 121 mm (4-3/4") plus or minus 11 mm (7/16") inlet/valve outlet centers
- Vacuum breaker
- Cover tube, wall flange, spud flange, concealed spud nut, and 292 mm (11-1/2") outlet tube
- Recommended water supply:**
Minimum flowing pressure – 25 psi (172 kPa)
Minimum flow rate – 25 gpm (95 L/min)

81T201SP-48-MMO

Same as 81T201SP-MMO, but factory set to 4.8 Lpf (1.27 gpf),
Not Field Adjustable



81T201SP-42-MMO

Same as 81T201SP-MMO, but factory set to 4.2 Lpf (1.1 gpf),
Not Field Adjustable



- 4.2 Lpf (1.1 gpf) valve is recommended for new construction only

APPROVALS:

- IAPMO listed to ASSE 1037/
ASME A112.1037/CSA B125.37
- Indicates compliance to
ICC/ANSI A117.1

(Contact Delta Representative for State and/or
Local Approvals.)

Patented




Engineer/Architect Approval

Model Specified:

Approval:

Date:

81T201SP-MMO



Note: For high and low pressure applications, please see page
FEA-81T High Water Pressure note for more details.
Verify flow requirements with bowl manufacturer.

Note: Measurements may vary \pm 6mm (0.25")

Refer to www.specselect.com for individual models.

Note: Use this page as a product submittal sheet.