

RESIDENTIAL PRODUCTS CATALOG 01.24



Thank goodness for Goodman.®



Thank goodness for Goodman®.



AWST | AIR HANDLER

WALL-MOUNT

AIR
HANDLERS

Model	Cooling (Tons)	Electric Heat	Voltage	Dimensions			Connection Size		Ship Weight (lbs)
				W"	D"	H"	Liquid"	Suction"	
AWST18SU1403	1½	3	208/230-1	20¾ ₁₆	16⅞	36	¾	⅝	84
AWST18SU1405	1½	5	208/230-1	20¾ ₁₆	16⅞	36	¾	⅝	84
AWST18SU1408	1½	8	208/230-1	20¾ ₁₆	16⅞	36	¾	⅝	84
AWST24SU1405	2	5	208/230-1	20¾ ₁₆	16⅞	36	¾	⅝	84
AWST24SU1408	2	8	208/230-1	20¾ ₁₆	16⅞	36	¾	⅝	84
AWST24SU1410	2	10	208/230-1	20¾ ₁₆	16⅞	36	¾	⅝	84
AWST30LU1405	2½	5	208/230-1	24	21	36	¾	¾	109
AWST30LU1408	2½	8	208/230-1	24	21	36	¾	¾	109
AWST30LU1410	2½	10	208/230-1	24	21	36	¾	¾	109
AWST36LU1405	3	5	208/230-1	24	21	36	¾	¾	109
AWST36LU1408	3	8	208/230-1	24	21	36	¾	¾	109
AWST36LU1410	3	10	208/230-1	24	21	36	¾	¾	109

Daikin Comfort Technologies Manufacturing, L.P. reserves the right to discontinue, or change at any time, specifications or designs without notice or without incurring obligations.

Standard Features

- AWST Models: Equipped with a fully adjustable TXV
- Direct-drive, multi-speed motors allows air volume variation for heating/cooling
- Sequence-controlled, rust-resistant nickel chromium heating elements of 3, 5, 8, and 10 kW
- Aluminum tubing coils on all models
- Cabinet air leakage less than 2.0% at 1.0 inch H₂O when tested in accordance with ASHRAE standard 193

Cabinet Features

- Cabinet air leakage less than 1.4% at 0.5 inch H₂O when tested in accordance with ASHRAE standard 193
- Factory-installed pull-type disconnect
- Thermoplastic drain pan with bottom primary and secondary drain connections
- Built-in filter rack (filter included)
- Large chassis (2½- and 3-ton units) – front return only
- Small chassis (1½- and 2-ton units) – front or bottom return
- Wall-hanging bracket provided
- AHRI Certified; ETL Listed



**10 PARTS
YEAR LIMITED
WARRANTY**

* Complete warranty details available from you local dealer or at www.goodmanmfg.com. To receive the 10-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. The duration of warranty coverages in Texas and Florida differs in some cases.