

POWERFUL CLEANING, SANITATION, AND DISINFECTION



INCLUDES
VACUUM



GVC-1502 & GVC-1502-VAC – Tough and Effective

For power, portability, and versatility, the GVC-1502 dry steam cleaner is a great choice. It comes in two configurations, with and without integrated wet vacuum for extraction. Use it to clean a large selection of surfaces in a variety of environments, including work tables, seats, carts, beds, carpets, upholstery, desks, door handles and more. All without chemicals and large volumes of water.

The secret is in the ultra-hot vapor steam. Its natural properties explosively loosen dirt, grease, and grime. It doesn't just clean. It also sanitizes your work surfaces. The high heat of the GVC-1502 kills bacteria, fungus, mold, mildew and other microorganisms on contact. An assortment of cleaning tools are included to suit a range of applications.

By design, dry steam uses minimal amounts of water, but for applications where residual water is unacceptable, the GVC-1502-VAC and its integrated vacuum will leave surfaces dry.

FEATURES

- Stainless steel construction
- Chemical-injection
- In operation refillable water tank
- Multiple cleaning tools
- Stainless steel boiler
- Integrated vacuum
- Adjustable dry steam volume

GVC-1502: Dry steam cleaner, including 8' hose with pistol grip, two-piece 38" wand, 11" floor brush, 5" triangular brush, 9 1/2" squeegee tool, 6 1/2" curved lance, 2" circular nylon brush, three circular nylon scrubbing brushes, three circular copper scrubbing brushes, three circular stainless steel scrubbing brushes, soap container and a 1 gallon bottle of cleaner.....

Call for Price

GVC-1502-VAC: Includes everything 1502 does, a 10' hose plus a variety of pickup tools to aid extraction. Note this product does not support chemical injection so does not include the soap container and bottle of cleaner.....

Call for Price

Note: Call or visit goodway.com for additional accessories.

| | GVC-1502 | GVC-1502-VAC |
|--------------------------------------|---|---|
| Input Power | 13 amps, 115V, 50/60 Hz AC, Maximum 1,500 W | 15 amps, 115V, 50/60 Hz AC, Maximum 1,800 W |
| Power Supply Cord | 14', 14-3 | 14', 14-3 |
| Max. Output Steam Pressure | 0 up to 90 PSI | 0 up to 90 PSI |
| Max. Output Steam Temperature | 290°F | 290°F |
| Output Steam Volume | 8 lbs/hour | 8 lbs/hour |
| Boiler | 0.8 gallons stainless steel | 0.6 gallons stainless steel |
| Water Tank | 1.3 gallons | 1.3 gallons |
| Chemical Tank | 1.3 gallons | - |
| Dimensions | 37" high x 13" wide x 21" deep | 36 1/2" high x 15" wide x 24" deep |
| Weight | 57 lbs net dry | 62 lbs net dry |

GOODWAY®
INNOVATIVE MAINTENANCE SOLUTIONS

Call: 1-800-333-7467
Visit: www.goodway.com

Goodway Technologies Corporation

420 West Avenue, Stamford, CT 06902-6384 U.S.A.

Phone: 203-359-4708 • Fax: 203-359-9601 • goodway@goodway.com