

Industrial & Commercial Portable Electric Heaters

NEED HEAT?

For Rental Services & **Temporary Heating Applications**



Temporary Heating **Solutions** For Any Job!

From smaller portable electric heaters to industrial & commercial units designed to heat large construction projects, we've got you covered.

Portable Electric Advantages

- 100% clean, dry heat no moisture added to air
- No exhaust can be used in confined spaces
- No need for gas line or propane
- Quiet operation
- Ductable & non-ductable models available

Applications

- Temporary heating for contractors & special events
- Emergency situations heat loss, thawing of frozen pipes

Capacity

5 kW / 7.5kW / 10kw / 15kW / 20kW / 25kW

All Units Provide Dry Heat Does Not Add Moisture To Environment

Portable Wheeled Unit Heater **PCKW Series**



UP TO 2500 SQ FT 34,100-85,250 BTU 1,000-1500 CFM





- Adjustable louvers
- Large capacity dual-inlet blower handles high static pressure
- Built-In thermostat (40°-100°F)
- Washable intake air filters
- Front and back carrying handles & heavy-duty pneumatic wheels
- Heat switch & fan only switch
- Long life 48 frame totally enclosed motor
- N.E.M.A. 12" gasket construction
- 6ft, SO cord (no plug)





Industrial Portable Unit Heater PKB-FM Series



UP TO 2000 SQ FT 17,100-68,200 BTU 400-1100 CFM

208/240/480V 5kW-20kW 1-3 Phase



- Stackable Design
- Adjustable louvers
- Built-in thermostat (40°-100°F)
- Carry handles & rubber feet
- Fan only switch
- 6ft. SO cord (no plug)







Portable Outdoor Rated Unit Heater **PCKF Series**

2Year Warrant_\

UP TO 2500 SQ FT 34,100-85,250 BTU 1,000-1500 CFM

208/240/480V 10kW-25kW 1-3 Phase



PKB-DT Series

LIMITED

2Year

*N*arrant^v

UP TO 1500 SO FT

17,100-51,200 BTU

400-925 CFM

208/240/480V

- Large capacity dual-inlet blower handles high static pressure
- Remote thermostat with 100' cord for temp control
- 24V control for heat or fan only
- High mass steel fin heat exchanger
- Long life 48 frame totally enclosed motor

Ducted Portable Unit Heater

N.E.M.A. 12" gasket construction





Electronic Portable Wheeled Unit Heater PKB Platinum Series



∠Year

UP TO 2000 SQ FT

25,600-68,200 BTU 400-1100 CFM

208/240/480V

7.5kW-20kW 1-3 Phase

Platinum electronic

Large LED display

Adjustable louvers

• 6ft. SO cord (no plug)

temperature sensing

Remote control included

Fan only & timer modes

Long life unit bearing motor

Spiral finned heat elements



208/240/480V 5kW-20kW 1-3 Phase





400-1100 CFM



Stainless steel for periodic hose - down

Built-in thermostat (40°-100°F)

Carry handles & rubber feet

Duct transition collar (8" 1PH, except 12/15kW / 12" 3PH Models)

₫ king

Spiral finned heat elements

5kW-15kW 1-3 Phase

- Built-in thermostat (40°-100°F)
- Carry handles & rubber feet
- Fan only switch
- 6ft. SO cord (no plug)













Adjustable louvers



WISA CO.



₫ king



High Velocity Drum Fans DFC Series



7300-17800 CFM 73-81 DB Noise Level



24" / 30" / 36" /42" / 48" 120V Belt Drive / Direct Drive

Features

- 2-Speed switch motor
- Aerodynamically balanced blades
- Convenient handles & rugged wheels
- Meets OSHA 1910.212(A)(5) requirements
- 9 ft, 120V grounded cord & plug
- Scratch resistant, powder- coated finish







8800-91000 CFM 74-76 DB Noise Level



24" / 30" 120V Direct Drive

Features

- 2-Speed pull chain switch
- 3 aerodynamically balanced blades
- Meets OSHA 1910.212(A)(5) requirements
- 9 ft, 120V grounded cord & plug
- Scratch resistant, powder- coated finish
- Adjustable height from 57" to 75"





REV 3-02-20

King Electrical Manufacturing Company 9131 10th Avenue South, Seattle WA 98108 phone 206.762.0400 fax 206.763.7738

king-electric.com



Mart Heating Solutions



Industrial & Commercial Portable Electric Heaters













	Item Number
	Category
	Application
	Max SqFt (8Ft Ceiling)
	Voltage
	Wattages Available (kW)
	Phasing Available
	Power Supply
	BTU Output
	CFM
	Energy-Saving 2-Stage Heating
	Built-In Thermostat
	Adjustable Louvers
	Power Indicator Light
	0N/0FF Switch
	High/Low
	Fan Only Switch
	Built-In Timer
	Element Construction
	High Limit Safety Control
	Auto Fan Delay
	Ductable
	Wet Location Rating
Ī	Instruction Manual
	Mounting Diagram
	Warranty
	Factory Tech Support

Made In USA

PKB-FM
Industrial Portable
Portable Large Facility Coverage
Up to 2,000 SqFt
208, 240, 480
5,000 - 20,000
1PH or 1-3Ph
Portable
17,100 - 68,200
400 - 1100
NO
Bi-Metal
YES
NO
NO
NO
YES
NO
Spiral Fin
Self-Hold
YES
NO
YES
YES
NO NO
2-Year
YES
NO
NO
YES

Pi	(B-DT
Indust	rial Portable
Portable Larg	e Facility Coverage
Up to	1,500 SqFt
208	, 240, 480
5,00	0 - 15,000
1PH	or 1-3Ph
P	ortable
17,10	0 - 51,200
40	0 - 925
	NO NO
В	i-Metal
1000	NO
//	NO
	NO
	NO NO
	YES
	NO NO
Sį	piral Fin
Se	elf-Hold
	YES
Ductat	ole On Outlet
	NO NO
	YES
	NO NO

YES NO

PKBS
Industrial Portable
Portable Large Facility Coverage
Up to 2,000 SqFt
208, 240, 480
5,000 - 20,000
1PH or 1-3Ph
Portable
17,100 - 68,200
400 - 1100
NO
Bi-Metal
YES
NO
NO NO
NO NO
YES
NO
Spiral Fin Stainless
Self-Hold
YES
NO
YES
YES
NO
2-Year
YES
NO
NO

Wheeled Industrial Portable
Portable Large Facility Coverage
Up to 2,500 SqFt
208, 240, 480
10,000 - 25,000
1PH or 1-3Ph
Portable
34,100 - 85,250
1000 - 1500
NO
YES
YES
NO
YES
NO
YES
NO
Spiral Fin
Auto Reset
YES
NO
NO
YES
NO
2-Year



