

# Handles

- Add handles on mobile units to improve maneuverability and ergonomics.
- Compatible with MetroMax® i, MetroMax® 4, and MetroMax® Q units.
- Corrosion-proof Type 304 stainless steel construction.



Tri-Lobal Adapters  
Included with handles.

## Tri-Lobal Adapter Replacements

Cat. No. MTLA

Bag of 4 assemblies

MTLA adapters are designed to work with MetroMax i, MetroMax 4, and MetroMax Q and are not compatible with original MetroMax.

## Extended Handle — {9.25}

Fits Shelf Depth (in.) (mm)		Extension Depth (Post to Edge of Handle) (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)		i, 4, and Q Cat. No.
18	457	4.5	113	2.5	1.1	MEH18S
24	610	4.5	113	2.8	1.3	MEH24S

NOTE: Stainless steel fasteners are provided with each handle to secure the handle to the post for heavier duty applications



## Easy-Grip Handle — {9.25}

Fits Shelf Depth (in.) (mm)		Extension Depth (Post to Edge of Handle) (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)		i, 4, and Q Cat. No.
18	457	6	151	2.5	1.1	MERGH18S
24	610	6	151	3.0	1.4	MERGH24S

NOTE: Stainless steel fasteners are provided with each handle to secure the handle to the post for heavier duty applications



## MetroMax® Stem Casters — {9.28}

For use with either polymer or steel stem caster posts.

- Promotes easy cleaning. Casters allow shelving units to be moved easily for access to floors and walls.
- Efficient Transport: Create a cart to efficiently move supplies throughout a facility or campus.

# Casters for Dry Areas



GOOD



5MPX

## Standard Stem Casters — {9.28}

- Plated caster horns and hardware. Bumper included with each caster.
- Swivel, Swivel with Brakes, and Rigid Caster options available.

Wheel Diameter (in.) (mm)	Face (in.) (mm)	Load Rating (lbs.) (kg)	Type	Wheel Tread	Temperature Range (Continuous Usage) (Fahrenheit) (Celsius)	Approx. Pkd. Wt. (lbs.) (kg)	Cat. No.
5 127	1 1/4 32	200 90	Stem/Swivel	Resilient, Flat	-20°-160° -29°-71°	2 1/2 1.1	5MX
5 127	1 1/4 32	200 90	Stem/Brake	Resilient, Flat	-20°- 160° -29°-71°	2 5/8 1.2	5MBX
5 127	1 1/4 32	200 90	Stem/Rigid*	Resilient, Flat	-20°- 160° -29°-71°	3 1/2 1.5	5MRX
5 127	1 1/4 32	250 113	Stem/Swivel	High Modulus Donut	-20°-180° -29°-82°	2 1/2 1.1	5MDXA
5 127	1 1/4 32	250 113	Stem/Brake	High Modulus Donut	-20°-180° -29°-82°	2 5/8 1.2	5MDBXA
5 127	1 1/4 32	250 113	Stem/Rigid*	High Modulus Donut	-20°-180° -29°-82°	2 5/8 1.1	5MDRXA
5 127	1 1/4 32	300 135	Stem/Swivel	Polyurethane, Flat	-20°-180° -29°-82°	2 1/8 0.9	5MPX
5 127	1 1/4 32	300 135	Stem/Brake	Polyurethane, Flat	-20°-180° -29°-82°	2 1/4 1	5MPBX
5 127	1 1/4 32	300 135	Stem/Rigid*	Polyurethane, Flat	-20°-180° -29°-82°	2 0.9	5MPRX

\*Note: Rigid casters are held in place by a connecting channel. When ordering, shelf width **must** be provided. Rigid connecting channel (stainless steel): Cat. No. 18RS, 21RS, or 24RS.

# Casters for Wet or Corrosive Areas


**GOOD**


5PCX



5PCBX

## Polymer Stem Casters — {9.28}

Corrosion resistance and enhanced durability. Appropriate for all medium-duty mobile applications. Bumpers included.

- All-polymer horn, stainless axle, and hardware. 5" (127mm) diameter polyurethane, flat wheel.
- Sleeve style axle bearing and optional toe-operated brake mechanism
- Antimicrobial options have a tread with built-in antimicrobial product protection.

Wheel Diameter (in.) (mm)	Face (in.) (mm)	Load Rating (lbs.) (kg)	Type	Temperature Range (Continuous Usage) (Fahrenheit) (Celsius)	Approx. Pkd. Wt. (lbs.) (kg)	Cat. No.	Cat. No. Antimicrobial
5 127	1.25 32	300 135	Stem/Swivel	-20°-120° -29°-49°	2 0.9	<b>5PCX</b>	<b>5PCXM</b>
5 127	1.25 32	300 135	Stem/Brake	-20°-120° -29°-49°	2 0.9	<b>5PCBX</b>	<b>5PCBXM</b>
5 127	1.25 32	300 135	Stem/Rigid*	-20°-120° -29°-49°	2 0.9	<b>5PCRX</b>	—

\*Note 1: Rigid casters are held in place by a connecting channel. When ordering, shelf width **must** be provided. Rigid connecting channel (aluminum) for 5PCRX caster: Cat. No. P18RC, P21RC, P24RC.

Note 2: Not suitable for cart wash and autoclave applications.


**BETTER**


5PSTE



5PSTEB

## Polymer & Stainless Total-Guard Casters — {9.28}

Corrosion Proof - nylon rig, Stainless stem, TPE wheel tread.

Break caster has total lock function. When the brake is engaged, the caster wheel and swivel are locked.

- Best for high humidity chambers, MRI areas, RFID storage
- Very good chemical resistance
- Good for cart wash chambers
- Quieter than polyurethane options

Wheel Diameter (in.) (mm)	Face (in.) (mm)	Load Rating (lbs.) (kg)	Type	Wheel Tread	Temperature range (continuous) (Fahrenheit) (Celsius)	Cat. No. Model No.
5 127	1.25 32	250 113	Stem/Swivel	TPE, Flat	-20° - 120° -29° - 49°	<b>5PSTEX</b>
5 127	1.25 32	250 113	Stem/Brake	TPE, Flat	-20° - 120° -29° - 49°	<b>5PSTEBX</b>


**BEST**


## Stainless Steel Cart-Washable Stem Casters — {9.28}

- Type 304 Stainless horn, axle, and stem with sealed bearings. Bumper included with each caster.

Wheel Diameter (in.) (mm)	Face (in.) (mm)	Load Rating (lbs.) (kg)	Type	Wheel Tread	Temperature Range (Continuous Usage) (Fahrenheit) (Celsius)	Approx. Pkd. Wt. (lbs.) (kg)	Cat. No.
5 127	1.25 32	300 135	Stem/Swivel	Polyurethane, Flat	-20°-180° -29°-82°	2.12 0.9	<b>5MPXGSA</b>
5 127	1.25 32	300 135	Stem/Brake	Polyurethane, Flat	-20°-180° -29°-82°	2.25 1	<b>5MPBXGSA</b>
5 127	1.25 32	300 135	Stem/Rigid*	Polyurethane, Flat	-20°-180° -29°-82°	2 0.9	<b>5MPRXGSA</b>

\*Note: Rigid casters are held in place by a connecting channel. When ordering, shelf width **must** be provided. Rigid connecting channel (stainless steel): Cat. No. 18RS, 21RS, or 24RS.

Rigid stem casters are often ordered two per unit for improved tracking and handling.  
Rigid caster channels are provided with each two rigid stem casters at no charge.



### Replacement Bumper

Tri-lobal polymer or steel post.  
Cat. No. M9992DBX



**CASTER  
INSTALLATION**