

WIRE STRIPPERS/CUTTERS



Strong gripping serrated nose for easy bending, shaping, and pulling of wire

Precision ground stripping holes

Wire looping and bending holes

Coil spring provides fast self-opening action

Handy closure lock for convenient storage

Screw shearing holes

Precision, shear-type cutting blades for easier cutting

Wire Strippers/Cutters

Includes core Wire Strippers/Cutters features plus:

- Easy-to-read markings
- Narrow nose fits into tight places
- Double dipped Klein Kurve™ comfort grips
- Glow-in-the-Dark grips to easily locate your tool in dark or low lit areas (Cat. No. 11055GLW)

HANDLE FINISH



Double-Dipped



GLOW-IN-THE-DARK Double-Dipped



INS INSULATED 2-Layer Protection



EINS INSULATED 3-Layer Protection



RINS INSULATED Thick Multi-Layer Protection



1000 V



1000 V



1000 V



K11095

KLEIN-KURVE®
comfort grip handles
for reduced hand fatigue

⚠ WARNING: Do NOT use for cutting steel wire or bolts

Strips and Cuts

Cat. No.	Solid AWG	Stranded AWG	NM-B Cable	NMD-90	Screw Shearing	Handle Color	Handle Finish	Overall Length
11053	—	6-12	—	—	6-32, 8-32	Blue/Red	Double-Dipped	7.5" (19.1 cm)
11054EINS	8-16	10-18	—	—	6-32, 8-32	Orange/Gray	3-Layer Insulation	7.7" (19.6 cm)
K11095	8-18	10-20	—	—	6-32, 8-32	Blue/White	Comfort Grip	7.25" (18.4 cm)
11055	10-18	12-20	—	—	6-32, 8-32	Blue/Yellow	Double-Dipped	7.4" (18.8 cm)
11055GLW	10-18	12-20	—	—	6-32, 8-32	Glow-in-the-Dark	Double-Dipped	7.4" (18.8 cm)
11055-INS	10-18	12-20	—	—	6-32, 8-32	Orange	2-Layer Insulation	7.7" (19.6 cm)
★ 11055RINS	10-18	12-20	—	—	6-32, 8-32	Orange/Light Gray	Thick Multi-Layer Insulation	7.7" (19.6 cm)
11057	20-30	22-32	—	—	6-32, 8-32	Blue/Red	Double-Dipped	7.5" (19.1 cm)
K1412	12-14	14-16	12/2, 14/2	—	6-32, 8-32	Yellow/White	Double-Dipped	8" (20.3 cm)
K1412CAN	12-14	14-16	—	12/2, 14/2	6-32, 8-32	Yellow/White	Double-Dipped	8" (20.3 cm)

Wire Strippers/Cutters/Crimpers

- Cuts and strips solid and stranded wire
- Crimps insulated and non-insulated connectors
- Cat. No. 1019 also crimps B-connectors and insulated displacement connectors (IDC)
- Tip designed to grab, pull and bend the smallest of wires
- Reinforced head reduces flex
- Optimized for ideal leverage when stripping and crimping
- Precision shear-type cutting blades for easier cutting
- Double dipped Klein Kurve™ comfort grips

⚠ WARNING: Do NOT use for cutting steel wire or bolts

KLEIN-KURVE®
comfort grip handles
for reduced hand fatigue



1019
Patent US D827,403




Insulated Connectors




Non-Insulated Connectors




B-Connectors



UR IDC
VDV826-605



UG IDC



UY IDC
VDV826-604

Strips and Cuts

Cat. No.	Solid AWG	Stranded AWG	Screw Shearing	Crimping Capacity	Handle Color	Handle Finish	Overall Length
1009	10-20	12-22	6-32, 8-32	10-22 AWG Insulated and Non-insulated Terminals	Gray/Yellow	Double-Dipped	7.75" (19.7 cm)
1019	10-26	12-28	6-32, 8-32	10-22 AWG Insulated and Non-insulated Terminals; B-Connectors; Scotchlok® IDC Connectors	Gray/Red	Double-Dipped	7.75" (19.7 cm)

Scotchlok® is a registered trademark of 3M Corporation.

