



- 1 - Tap Buttons
- 2 - Infusion Dials
- 3 - Nozzles
- 4 - Exterior
- 5 - Inlet Connector
- 6 - Main ON/OFF Switch
- 7 - Legs

- 8 - Forward Plate
- 9 - Rear Plate
- 10 - Side Panel(s)
- 11 - Power Cord
- 12 - Vents/Exhaust
- 13 - Control Panel
- 14 - Beverage Tube

- 15 - Elbow Connectors
- 16 - Pre-Filter
- 17 - BROOD Beverage Container
- 18 - Inlet for Container
- 19 - Thermostat
- 20 - Calibration Knob
- 21 - Inlet Air...?

SPECIFICATIONS

SPECS	DUAL
FUNCTION	COLD NITRO & COLD STILL
TAPS	2
POWER SUPPLY	100-120V / 60HZ 200-240V / 50-60HZ
PHASE	SINGLE
AMPS	3.0A
DIMENSIONS (W/H/D)	9.25/14.74/18.25IN
WEIGHT	78LBS
DISPENSING CAPACITY	102 L/HOUR PER TAP
COFFEE TEMPERATURE AT TAP	36°F (+/- 3°F)
INTERNAL TUBING CAPACITY	20 OZ PER TAP
OPTIONAL ACCESSORIES	BIB BAGS BIB BOXES 1.5 GAL RESERVOIR 3.5 GAL RESERVOIR
WARRANTY	1 YEAR
PRESSURE AT TAP	34 PSI
INPUT BEVERAGE	READY-TO-DRINK (RTD)
WATER ACCESS	NO
WATER ACCESS INLET	N/A
DRAINAGE	NOT REQUIRED
RATIO RANGE	N/A
DISPENSE OPTIONS	PUSH BUTTON TAP HANDLE

FEATURES

Dispenses both nitro and still cold brew from the same tap
Extracts nitrogen from the air; no nitrogen tank necessary

Pulls from any container, kegs are only one option

Plug & play in 2 minutes

Consistency with every pour

Chills on demand to 36°F

Works with any drink

No need to deal with gas tanks or companies

Compact design; can be placed over or under the counter
Customizable color, design and tap handle

Patent Pending

In-line dosing pump that works with all ratios of cold brew concentrates

120 VOLT W/CORD & PLUG

1909 ALBION RD
TORONTO ON, CANADA
M9W 5S8

(647) 915-7771
hello@drinkbrood.com
drinkbrood.com