

Product Description - Extra Grip Additive is a non-skid paint additive that can be easily added to most floor paints and coatings to provide better grip and increase traction on indoor and outdoor surfaces. Extra Grip creates a safe, skid-resistant finish while retaining the color, coverage and performance of your coating. Compatible with most epoxy, urethane, and acrylic coatings, both water- and solvent-based.
NOT RECOMMENDED FOR USE IN CLEAR COATINGS.

SlipDoctors Extra Grip Slip Resistant Additive

Special Features

- Interior and Exterior Use
- Increases Traction
- Durable Anti-Slip Finish
- Easy to Use
- Barefoot Friendly
- Paw Friendly
- Chemical Resistant

Suggested Uses

- Patios
- Garage Floors
- Driveways
- Walkways
- Steps & Stairs
- Ramps
- Residential & Commercial

Product Characteristics and Benefits

Surfaces	Compatible with color paints and coatings. Use with Acrylic, Latex, Urethane, Epoxy and other oil- and water-based color coatings.
Color	Light Gray
Container Size	12-ounce bottle (340 grams)
Product Type	Ground Pumice
Coverage	One container (12 ounce / 340 grams) per gallon
Mode of Application	Follow coating manufacturer's instructions.
Dry Time	Follow coating manufacturer's instructions.
Water Resistant	Yes
Storage	Store unused Extra Grip tightly sealed in a cool dry place away from humidity. Unused mixed product can be stored according to coating manufacturer's instructions.
Shelf Life	5 years
Warranty	N/A
Removal	Follow coating manufacturer's instructions for removal.
Disposal	Dispose of container and unused contents in accordance with local, state and federal regulations.

Directions for Preparation, Application and Use

Read entire product label, Technical Data Sheet (TDS) & Safety Data Sheet (SDS) before using.

Surface Preparation

Follow the coating or paint manufacturer's instructions for surface preparation.

Application Instructions

1. Mix Extra Grip with coating in a separate container. Use one 12 oz container per gallon.
2. Mix thoroughly into paint until an even and consistent mixture is achieved.
3. Apply using a 3/8" to 3/4" nap roller following coating manufacturer's application instructions. Stir occasionally to ensure that particles are well distributed throughout mixture.
4. When applying two coats, Extra Grip can be used in both coats.
5. Follow coating manufacturer's instructions for dry times and clean up.

Precautions & Technical Support

Please refer to Safety Data Sheet (SDS) for detailed Precautions and First Aid Instructions.

Technical Support: Please contact SlipDoctors at 1-888-436-5404 or support@slipdoctors.com

Office Hours: Monday-Friday from 8:00 am – 5:00 pm CT.

Warranty & Disclaimer

Warranty not applicable for this product. Please refer to coating manufacturer for warranty information.