HOBART

Undercounters – Machine Configuration and Model Mix







LXnR advansýs^{*}

13 / 24 / 30 / 48* RPH *(With 2nd Level Rack)







LX*n*H

15 / 32 / 48* RPH *(With 2nd Level Rack)

LXnC

15 / 34 / 48* RPH *(With 2nd Level Rack)















| Features ▼ | LXnR advansýs | LXnH/LXnC Base | LXGnR/LXGnPR ADA Compliant advansýs | CUH/CUL |
|--|-------------------------|-------------------------|--|-------------------------|
| NSF Certified Pot & Pan Cycle | ✓ | - | - | - |
| Steam Elimination & Energy Recovery | ✓ | _ | (LXG <i>n</i> R) | - |
| Two-Level Racking Capability | ✓ | √ | - | - |
| Smart Touchscreen Controls | ✓ | ✓ | ✓ | - |
| WiFi Connectivity | ✓ | ✓ | ✓ | - |
| SmartConnect App | ✓ | ✓ | ✓ | - |
| Two-Stage Filtration | ✓ | ✓ | ✓ | - |
| AutoClean | ✓ | ✓ | √ | - |
| Sense-A-Temp Integrated Booster | ✓ | (LX <i>n</i> H) | (LXG <i>n</i> R) | (CUH) |
| Low Chemical Alert | ✓ | √ | √ | ACC |
| Door Opening Height | 17" | 17" | 12" | 14.46" |
| Delime Cycle | Auto | Notification/ Manual | Auto (LXG <i>n</i> R) Notification/ Manual (LXG <i>n</i> PR) | Notification/ Manual |