SC750/SC800 How To									
Prepare for use									
1	This is how the machine should look when you enter the room.		Unplug battery charger. Wrap cord accordingly.	3	Inspect recovery tank and ball float cage then lower the lid.				
4	Fill solution tank with water (do not exceed 130°F). Add appropriate cleaning chemical.		Do not mix detergent in the tank for EcoFlex models (fill cartridge).	6	Inspect squeegee blade, install squeegee on machine (attach recovery hose to the squeegee inlet).				
7	Inspect and install brush or pad.		Install brush or pad- holder under the deck.	9	Install brush for (<i>Cylindrical models</i>).				
10	Safely transport machine to desired work location.		Turn on machine. Verify there is enough battery life to complete job. Choose appropriate controls for the job.	12	Turn on scrub switch, lower squeegee and begin scrubbing.				



SC750/SC800 How To								
Store the Machine								
1	Empty recovery tank and solution tank. Empty water in suitable drain or bucket.	2	Wash recovery tank and solution tank thoroughly with clean water.	3	Inspect and clean vacuum shut off and debris catch cage.			
4	Inspect hoses; replace if kinked or damaged.	5	Remove, rinse and inspect squeegee. Replace if needed.	6	Remove, clean and inspect brush or pad. Rinse with warm water. Hang to dry. Replace if needed.			
7	Lift recovery tank lid. Allow tank to air dry.Lift recovery tank lid. Allow tank to air dry. <td>8</td> <td>Charge batteries.</td> <td>9</td> <td>Wipe down exterior of the machine.</td>	8	Charge batteries.	9	Wipe down exterior of the machine.			



SC750/SC800 How To								
	Daily Maintenance							
1 Charge Batteries daily at the end of the shift.	2 Check/clean tanks and hoses. Inspect ball float cage.	Respect and clean debris catch cage.						
4 Check, clean and rotate the brushes/pads.	5 Clean and check the squeegee.	Clean Hopper on (<i>Cylindrical models</i>).						
	Weekly Maintenance							
1 Inspect scrub housing skirts.	2 Inspect and clean solution filter.	Check each battery cell water level (does not apply to gel batteries).						
4 Clean solution manifolds on Cylindrical models.	5 Purge EcoFlex System: Disconnect and remove cartridge, turn machine ON. Press and hold the solution switch for 2 seconds.	Marth: Tealtic bifters by fully target more an user Marth: Tealtor after 500 Blarx: inget Barbon trades on vice and more Marth: Tealtor after 500 Blarx: inget Barbon trades on vice and more Marth: Tealtor after 500 Blarx: inget Barbon trades on vice and more Marth: Tealtor after 500 Blarx: inget Barbon trades on vice and more Marth: Tealtor after 500 Blarx: inget Barbon trades on vice and branch Marth: Tealtor after 500 Blarx: inget Barbon trades on vice and branch Barbon trades on vice and vice and vice and vice and vice and						

