

#600SL35

Commercial ScrapLock™

Drain Protection Starts at the Sink

Drain clogs can be a time-consuming and costly problem to fix. The ScrapLock™ 3½" locking drain strainer is the perfect piece of equipment to keep food and debris from blocking your drains.



Saves Time and Money

Prevents costly clogs, backups, and other drain emergencies.



Simple and Secure Installation

Quick installation that locks in sinks for tamper-proof operation that blocks solids and debris immediately.



Improves Efficiency

Reduces grease trap maintenance, prolongs pump outs, and improves wastewater.

Assembly Instructions

1. Line up the 2 feet of the ScrapLock™ with the openings of the ring in your commercial sink drain. The guard should be seated flush with the top of the drain. (Fig. 1)
2. Using the set screw as a handle, turn the guard 90° clockwise. This secures the feet under the ring rim and positions the set screw directly over one of the groove openings. (Fig. 2)
Note: If unable to turn guard during this step, loosen each foot a half turn to extend the height.
3. Use the included Allen wrench to tighten down the set screw until the top is recessed slightly into the guard. This positions the set screw in the groove opening and secures the guard in place. (Fig. 3)
4. Place the small plastic cap into the top of the set screw head. (Fig. 4)
5. The ScrapLock™ guard is now fully installed.

Fig. 1



Fig. 2



Fig. 3



Fig. 4

