

LIMITED WARRANTY

Manufacturer warrants, to the purchaser and subsequent owner during the warranty period, every new product to be free from defects in material and workmanship under normal use and service, when properly used and maintained, for a period of two years from the date of purchase. Proof of purchase is required. Parts that fail within the warranty period, that inspections determine to be defective in material or workmanship, will be repaired, replaced or remanufactured at Manufacturer's option, provided however, that by so doing we will not be obligated to replace an entire assembly, the entire mechanism or the complete unit. No allowance will be made for shipping charges, damages, labor or other charges that may occur due to product failure, repair or replacement.

This warranty does not apply to and there shall be no warranty for any material or product that has been disassembled without prior approval of Manufacturer, subjected to misuse, misapplication, neglect, alteration, accident or act of God; that has not been installed, operated or maintained in accordance with Manufacturer's installation instructions; that has been exposed to outside substances including but not limited to the following: sand, gravel, cement, mud, tar, hydrocarbons, hydrocarbon derivatives (oil, gasoline, solvents, etc.), or other abrasive or corrosive substances, wash towels or feminine sanitary products, etc. in all pumping applications. The warranty set out in the paragraph above is in lieu of all other warranties

expressed or implied; and we do not authorize any representative or other person to assume for us any other liability in connection with our products.

Contact Manufacturer at, 3649 Cane Run Road, Louisville, Kentucky 40211, Attention: Customer Service Department to obtain any needed repair or replacement of part(s) or additional information pertaining to our warranty.

MANUFACTURER EXPRESSLY DISCLAIMS LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL DAMAGES OR BREACH OF EXPRESSED OR IMPLIED WARRANTY; AND ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY SHALL BE LIMITED TO THE DURATION OF THE EXPRESSED WARRANTY.

Some states do not allow limitations on the duration of an implied warranty, so the above limitation may not apply to you. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

In instances where property damages are incurred as a result of an alleged product failure, the property owner must retain possession of the product for investigation purpose.

NOTE: Ratings based on 1-1/4" pipe with friction loss neglected. Using 3/4" garden hose adapter, performance will be reduced approximately 15%. This pump does not deliver enough pressure to operate lawn sprinklers properly.

OPERATION

1. Set pump on hard surface in water before starting.
2. Use the included garden hose adapter for 3/4" discharge line or disconnect the adapter to use a 1-1/4" discharge.
3. Plug power cord into properly grounded 115 volt AC power outlet. (See recommended grounding methods on front page). Will operate continuously whether partly or fully submerged. Submersible utility pumps are intended to pump water at temperatures up to 104 °F (40 °C).

For automatic model LM44 only:

4. When the pump senses that it is no longer pumping water, the pump will shut off automatically. The pump will then turn on every three minutes for 5 seconds and then off if it does not sense any water.
5. If water is sensed after the pump begins running, the pump will continue pumping until the pump senses that it is no longer pumping water.
6. Unplug the pump from the power output when not in use.
7. The pump is supplied with a 3/4" garden hose adapter. For use with plastic pipe, remove the adapter and install the desired 1-1/4" NPT fitting. DO NOT OVERTIGHTEN THE HOSE OR PLASTIC ADAPTER FITTING. Finger tight plus 1/2 turn is sufficient.

CAUTION

Extended usage of the pump in a partially submerged or non-submerged situation may cause the pump to overheat due to lack of heat dissipation from the water. If this occurs, the pump will shut itself off until the motor cools to its normal temperature. Repeated overheating may cause damage to the pump.

MAINTENANCE

1. The motor housing of the pump is completely sealed and requires no service. Disassembly of the motor housing or alteration of the power cord voids all warranty.
2. The motor is a continuous duty type with an automatic thermal overload protector device.
3. The pump can run against a partially restricted discharge, but is designed to move large volumes of water with minimal back pressure.
4. If the pump becomes clogged, remove the screen and clean out the area.
5. Debris in the intake should be routinely removed from the bottom of the pump to prevent damage to the pump, which will void the warranty.
6. If necessary, remove the eight (8) screws holding the volute base to the motor housing and clean the volute.

CAUTION

Do not set pump directly on sand, dirt or mud. Sand or mud-choked pumps can be back-flushed clean.

CAUTION

Do not handle or carry the pump by the power cord. Use the handle.

ZOELLER
PUMP COMPANY



MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

Trusted. Tested. Tough.®

Visit our web site:
zoellerpumps.com