

Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Revision date: 02/01/2018

Product name: Lithium ion Battery

Printing date: 02/01/2018

1. Identification

(a) Product identifier

Product name: Lithium ion batteries

(b) Other means of identification

Product description:

Model	INR 18650 8000mAh 48V
Nominal Voltage	48V
Ampere-hour	8.0Ah
Typical Capacity	8000mAh
Weight	2500 ± 10g
Dimension	197.5 ± 1mm x 136 ± 1mm x 62 ± 2mm (L x W x H)

(c) Recommended use of the chemical and restrictions on use

Recommended use: Battery.

Restriction on use: No information available.

(d) Details of the supplier of the product

Company name(China)	Wintonic Battery&Magnet Company Limited
Address	#38, YunFeng Road, XinHua Industrial Zone, Huadu District, Guangzhou, China
E-mail	Dqf5crystal@126.com
Telephone	+86-020-36865508

2. Hazard(s) identification

(a) Classification of the chemical

The batteries are defined as “articles”, they are exempted from the requirements of the Hazard Communication Standard. A sealed Lithium ion battery is not hazardous in normal use.

(b) Label elements

Pictogram(s)	No pictogram
Signal word	No signal word
Hazard statements	No hazard statement
Precautionary statements	No precautionary statement

(c) Description of any hazards not otherwise classified

In case of mistreatment (abusive over charge, reverse charge, external short circuit...) and in case of

Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Revision date: 02/01/2018

Product name: Lithium ion Battery

Printing date: 02/01/2018

fault some electrolyte can leak from the cell through the safety device. In these cases refer to the risk of the electrolyte. Contact with internal components may cause irritation or severe burns. Irritating to eyes, respiratory system, and skin. The electrode materials are only hazardous, if the materials are released by mechanical damaging of the cell or if exposed to fire.

Skin touch: Contact with battery electrolyte may cause burns and skin irritation.

Eyes touch: Contact with battery electrolyte may cause burns. Eye damage is possible.

Inhalation: Inhalation of a large number of vapors or fumes released due to hear may cause respiratory.

Ingestion: Ingestion of battery contents may cause mouth, throat and intestinal burns and damage.

(d) Ingredient with unknown acute toxicity

No information available.

3.Composition/information on ingredients

Mixtures information

Chemical name	CAS No.	Concentration%
Graphite	7782-42-5	16.73%
Copper	7440-50-8	11.58%
Iron	7439-89-6	19.81%
Aluminum	7429-90-5	5.36%
Nickel	7440-02-0	0.95%
Lithium Cobalt Oxide(CoLiO_2)	12190-79-3	2.24%
Manganese oxide(MnO)	1344-43-0	8.44%
Cobalt oxide	11104-61-3	5.88%
Nickel oxide	1313-99-1	14.66%
Sodium carboxymethyl cellulose	9004-32-4	0.37%
Butadiene-styrene copolymer	9003-55-8	0.40%
Polyvinylidene Fluoride	24937-79-9	0.65%
Polypropylene	9003-07-0	2.39%
Ethylene carbonate(EC)	94-49-1	3.22%
Dimethyl carbonate	616-38-6	3.22%
Diethyl carbonate(DEC)	105-58-8	3.22%
Phosphate(1-), hexafluoro-, lithium	21324-40-3	0.88%

4.First-aid measures

(a) Description of first aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable
------------	---

Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Revision date: 02/01/2018

Product name: Lithium ion Battery

Printing date: 02/01/2018

	for breathing. Get medical advice / attention if you feel unwell.
Skin contact	Remove contaminated clothes and rinse the skin with plenty of water. Get medical advice / attention if you feel unwell.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice / attention if you feel unwell.
Ingestion	Have victim drink 60 to 240 ml (2-8 oz.) of water, and DO NOT induce vomiting. Get medical aid.

(b) Most important symptoms/effects, acute and delayed

Contact with internal components may cause allergic skin sensitization (rash) and irritate eyes, skin, nose, throat, respiratory system. Cobalt and Cobalt compounds are considered to be possible human carcinogen(s).

(c) Immediate medical attention and special treatment

No information available

5. Fire-fighting measures

(a) Extinguishing media

Suitable extinguishing media: Use foam, dry powder or dry sand, CO₂ as appropriate.

Unsuitable extinguishing media: No information available.

(b) Special hazards arising from the chemical

Under fire conditions, batteries may burst and release hazardous decomposition products when exposed to a fire situation. This could result in the release of flammable or corrosive materials.

Hazardous combustion products: CO, CO₂, Metal oxides, Irritating fumes.

(c) Special protective equipment and precautions for fire-fighters

Firefighters must wear fire resistant protective equipment and appropriate breathing apparatus. The staff must equip with filtermask (full mask) or isolated breathing apparatus. The staff must wear the clothes which can defense the fire and the toxic gas. Put out the fire in the upwind direction. Remove the container to the open space as soon as possible. Spray water on the containers in the fireplace to keep them cool until finish extinguishment.

6. Accidental release measures

(a) Personal precautions, protective equipment and emergency procedures

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area, dispose the case after the batteries cool and vapors dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors.

Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Revision date: 02/01/2018

Product name: Lithium ion Battery

Printing date: 02/01/2018

(b) Methods and materials for containment and cleaning up

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

7. Handling and storage

(a) precautions for safe handling

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types. Keep batteries away from children. For devices to be used by children, the battery casing should be protected against unauthorized access. Unpacked batteries shall not lie about in bulk. In case of battery change always replace all batteries by new ones of identical type and brand. Do not swallow batteries. Do not throw batteries into water. Do not throw batteries into fire. Avoid deep discharge. Do not short-circuit batteries. Use recommended charging time and current.

(b) Conditions for safe storage, including any incompatibilities

If the Lithium ion Batteries is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Lithium ion Batteries periodically. Operating temperature: Charge: 0°C~45°C. Discharge: -20°C~60°C and recommended at -20°C~45°C for 1 month storage, at -20°C~35°C for 3 months storage. The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more. The voltage for a long time storage shall be 7.4V~8.4V range. Do not storage Lithium ion Batteries haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects. Keep out of reach of children.

8. Exposure controls/personal protection

(a) Control parameters

Not established.

(b) Appropriate engineering controls

Under normal conditions (during charge and discharge) release of ingredients does not occur.

(c) Personal protective equipment

Respiratory protection	No personal respiratory protective equipment normally required. In case of inadequate ventilation wear respiratory protection
Hand protection	Wear protective gloves
Eye/face protection	No personal protective equipment normally required
Skin/body protection	Wear protective clothing to prevent contact

Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Revision date: 02/01/2018

Product name: Lithium ion Battery

Printing date: 02/01/2018

9. Physical and chemical properties

Appearance	Square solid
Odor	Monotony
Odor threshold	Not available
pH	Not available
Melting point/freezing point	Not available
Initial boiling point and boiling range	Not available
Flash point	Not applicable
Evaporation rate	Not applicable
Flammability	Not flammable
Upper/lower flammability or explosive limits	Not available
Vapor pressure	Not applicable
Vapor density	Not available
Relative density	Not available
Solubility(ies)	Insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	130°C
Decomposition temperature	Not available
Viscosity	Not available

10. Stability and reactivity

(a) Reactivity

Stable under recommended storage and handling conditions.

(b) Chemical stability

Stable under normal conditions.

(c) Possibility of hazardous reactions

When heated above 150°C the risk of rupture occurs. Due to special safety construction, rupture implies controlled release of pressure without ignition.

(d) Conditions to avoid

Do not subject Lithium ion Batteries to mechanical shock. Keep away from open flames, high temperature.

Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Product name: Lithium ion Battery

Revision date: 02/01/2018

Printing date: 02/01/2018

(e) Incompatible materials

Strong oxidizer, strong acid.

(f) Hazardous decomposition products

Under fire conditions, the electrode materials can form carcinogenic nickel and cobalt oxides.

11. Toxicological information

(a) Information on the likely routes of exposure

Inhalation	Inhalation of a large number of vapors or fumes released due to heat may cause respiratory
Ingestion	Ingestion of battery contents may cause mouth, throat and intestinal burns and damage
Skin contact	Contact with battery electrolyte may cause burns and skin irritation
Eye contact	Contact with battery electrolyte may cause burns. Eye damage is possible

Under normal conditions (during charge and discharge) release of ingredients does not occur. If accidental release occurs see information in section 2,3, and 4. Swallowing of a battery can be harmful. Call the local Poison Control Centre for advice and follow-up.

(b) Information on toxicological characteristics

Acute toxicity	No data available
Skin corrosion / irritation	The liquid in the battery irritates
Serious eye damage / irritation	The liquid in the battery irritates
Respiratory sensitization	The liquid in the battery may cause sensitization to some person
Skin sensitization	The liquid in the battery may cause sensitization to some person
Carcinogenicity	Cobalt and Cobalt compounds are considered to be possible human carcinogen(s)
Germ Cell Mutagenicity	No data available
Reproductive Toxicity	No data available
STOT-Single Exposure	No data available
STOT-Repeated Exposure	No data available
Aspiration Hazard	No data available

12. Ecological information

(a) Ecotoxicity

Water hazard class 1(Self-assessment): slightly hazardous for water.

(b) Persistence and Degradability

No information available.

Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Revision date: 02/01/2018

Product name: Lithium ion Battery

Printing date:02/01/2018

(c) Bioaccumulative potential

No information available.

(d) Mobility in soil

No information available.

(e) Other adverse effects

No information available.

13. Disposal considerations

Safe handling and methods of disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

14. Transport information

According to PACKING INSTRUCCION 965~970 of IATA DGR 56rd Edition for transportation, the special provision 188 of IMDG (inc Amdt 35-10). The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport.. Take in a cargo of them without falling,dropping, and breakage.Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area and congested area. Forbid to use wooden, cement for bulk transport.

UN number	3480&3481
UN Proper shipping name	LITHIUM ION BATTERIES (including lithium ion polymer batteries) or ;LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT OR LITHIUM ION BATTERIES PACKED WITH EQUIPMETN(including lithium ion polymer batteries
Transport hazard class(es)	9
Packing group (if applicable)	II
Marine pollutant (Yes/No)	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	No information available
Special precautions	No information available

Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Product name: Lithium ion Battery

Revision date: 02/01/2018

Printing date:02/01/2018

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

CAS No.	USA TSCA	EU EINECS	Japan ENCS	Korea ECL	China IECSC	Canada DSL
7782-42-5	Listed	Listed	Not Listed	Listed	Listed	Listed
7440-50-8	Not Listed	Listed	Listed	Listed	Listed	Not Listed
7439-89-6	Listed	Listed	Listed	Listed	Listed	Not Listed
7429-90-5	Listed	Listed	Not Listed	Listed	Listed	Listed
7440-02-0	Not Listed	Listed	Listed	Listed	Listed	Not Listed
12190-79-3	Listed	Listed	Listed	Listed	Listed	Listed
1344-43-0	Listed	Listed	Listed	Listed	Listed	Listed
11104-61-3	Listed	Listed	Listed	Listed	Listed	Listed
1313-99-1	Not Listed	Listed	Not Listed	Listed	Listed	Not Listed
9004-32-4	Listed	Listed	Listed	Listed	Listed	Listed
9003-55-8	Listed	Not Listed	Listed	Listed	Listed	Listed
24937-79-9	Listed	Not Listed	Listed	Listed	Listed	Listed
9003-07-0	Listed	Listed	Listed	Listed	Listed	Listed
96-49-1	Listed	Listed	Not Listed	Listed	Listed	Not Listed
616-38-6	Listed	Not Listed	Not Listed	Not Listed	Listed	Not Listed
105-58-8	Listed	Not Listed	Not Listed	Listed	Not Listed	Not Listed
21324-40-3	Not Listed	Listed	Listed	Listed	Listed	Not Listed

16. Other information, including date of preparation or last revision

(a) Preparation and revision information

Date of previous revision: Not applicable.

Date of this revision: 04/02/2015

Revision summary: The first New SDS

(b) Abbreviations and acronyms

TSCA	Toxic Substances Control Act, The American chemical inventory
DSL	Domestic Substances List
EINECS	European Inventory of Existing Commercial chemical Substances
ENCS	Japanese Existing and New Chemical Substances
ECL	Existing Chemicals List, the Korean chemical inventory
IECSC	Inventory of existing chemical substances in China

(c) Disclaimer

Safety Data Sheet

According to HCS-2012 APPENDIX D TO §1910.1200

Version: 1.0/EN

Revision date: 02/01/2018

Product name: Lithium ion Battery

Printing date:02/01/2018

Because all of our batteries are defined as “articles”, they are exempted from the requirements of the Hazard Communication Standard. The information in this SDS is provided all the relevant data fully and truly. However, the information is provided without any warranty on their absolute extensiveness and accuracy. This SDS was prepared to provide safety preventive measures for the users who have got professional training. The personal user who obtained this SDS should make independent judgment for the applicability of this SDS under special conditions. In these special cases, we do not assume responsibility for the damage.

-----End of the SDS-----