



Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard
Issue date: 12/19/2023 Revision date: 4/10/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name : FLEX CAULK AEROSOL WHITE
Product code : CFSWHTR100 & CFSWHTR675
Product form : Mixture

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives, binding agents
Restrictions on use : None

1.3. Supplier

UNITED STATES	CANADA
Swift Response LLC. 15499 SW 12th Street, Sunrise, FL 33326	Swift Response LLC. 277 Humberline Drive Toronto, ON M9W 0B6

1.4. Emergency telephone number

Emergency number : Chemtrec (800) 424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Gases under pressure Compressed gas	H280	Contains gas under pressure; may explode if heated
Eye irritation Category 2A	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Reproductive toxicity Category 1B	H360	May damage the unborn child.
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs (respiratory tract) through prolonged or repeated exposure (Inhalation)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H280 - Contains gas under pressure; may explode if heated
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H360 - May damage the unborn child.
H373 - May cause damage to organs (respiratory tract) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe vapors.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, eye protection.
P302+P352 - If on skin: Wash with plenty of water.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P314 - Get medical advice/attention if you feel unwell.
P405 - Store locked up.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Calcium Carbonate	CAS-No.: 1317-65-3	15 - 60
Titanium Dioxide	CAS-No.: 13463-67-7	1 - 5
Stearic acid	CAS-No.: 57-11-4	1 - 5
Trimethoxyvinylsilane	CAS-No.: 2768-02-7	1 - 5
N-(3-(trimethoxysilyl)propyl)ethylenediamine	CAS-No.: 1760-24-3	<2
Dibutylbis(pentane-2,4-dionato-O,O')tin	CAS-No.: 22673-19-4	< 1
Silicon Dioxide, Quartz	CAS-No.: 14808-60-7	< 1
Nitrogen	CAS-No.: 7727-37-9	< 1
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	CAS-No.: 52829-07-9	< 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If symptoms persist, call a physician.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause minor irritation to the respiratory tract and to other mucous membranes. Causes serious eye irritation. May cause slight irritation to the skin. May cause an allergic skin reaction. May cause damage to organs (respiratory system) through prolonged or repeated exposure (inhalation). May damage the unborn child. Suspected of damaging fertility.
Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: May cause slight irritation to the skin. May cause an allergic skin reaction.
Eyes	: Causes serious eye irritation.
Ingestion	: No adverse effects expected under normal conditions of use. Irritation to the digestive tract.
Chronic symptoms	: May cause damage to organs. May damage the unborn child. Suspected of damaging fertility.

4.3. Immediate medical attention and special treatment, if necessary

None under normal conditions.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Alcohol-resistant foam. Water spray. Dry powder. Carbon dioxide.
Unsuitable extinguishing media	: Not determined.

5.2. Specific hazards arising from the chemical

Fire hazard	: This product is not classified as flammable or combustible. Pressurized container: may burst if heated.
Explosion hazard	: Intense heat may cause container to burst.
Hazardous decomposition products in case of fire	: Toxic vapors may be released. Carbon oxides (CO, CO ₂). Silicon oxides. Metal oxides.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ventilate area. Avoid contact with eyes, skin and clothing. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Do not breathe vapors. Keep unnecessary and unprotected personnel away from the spillage. Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

6.2. Environmental precautions

Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Ventilate area. Take up liquid spill into absorbent material. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Use personal protective equipment as required.
Other information	: Polymerizes slowly on exposure to air. Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of contaminated materials refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Ensure adequate ventilation. Do not breathe vapors. Avoid contact with eyes, skin and clothing. Wear personal protective equipment. Contents under pressure. Do not puncture or incinerate containers. Handle in accordance with good industrial hygiene and safety procedures.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up. Store in a well-ventilated place. Keep away from heat and direct sunlight. Protect from physical damage. U.F.C. (NFPA 30B) Level I Aerosol.
Incompatible materials	: Store away from strong oxidizers, strong bases, strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium Dioxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH OEL TWA	0.2 mg/m ³ (Nanoscale particles. R - Repairable particulate matter) 2.5 mg/m ³ (Finescale particles. R - Repairable particulate matter)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Titanium Dioxide (13463-67-7)	
OSHA PEL (TWA)	15 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Calcium Carbonate (1317-65-3)	
USA - OSHA - Occupational Exposure Limits	
Local name	Calcium Carbonate (Limestone; Marble)
OSHA PEL (TWA)	15 mg/m ³ (Total dust) 5 mg/m ³ (Respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Silicon Dioxide, Quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Silica crystalline - quartz
ACGIH OEL TWA	0.025 mg/m ³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Quartz (Respirable) (Silica: Crystalline)
OSHA PEL (TWA)	0.05 mg/m ³ respirable dust
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO ₂ +5)) for mppcf and (10 mg/m ³ / (%SiO ₂ +2)) for mg/m ³ . CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
Stearic acid (57-11-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Stearic acid
ACGIH OEL TWA	10 mg/m ³ (I - Inhalable particulate matter) 3 mg/m ³ (R - Respirable particulate matter)
Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2024
Nitrogen (7727-37-9)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Nitrogen
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant
Regulatory reference	ACGIH 2024

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure adequate ventilation.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Hand protection:

Wear suitable gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Not required for normal conditions of use. [In case of inadequate ventilation] wear respiratory protection.

Thermal hazard protection:

Not applicable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol can. White. Paste.
Color	: White
Odor	: Odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.51 – 1.64
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: Product is not explosive. Pressurized container: may burst if heated.
Oxidizing properties	: Not oxidising.

9.2. Other information

Gas group : Compressed gas

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
 Acute toxicity (dermal) : Not classified
 Acute toxicity (inhalation) : Not classified

Trimethoxyvinylsilane (2768-02-7)

LC50 Inhalation - Rat (Vapours)	16.8 mg/l/4h
---------------------------------	--------------

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

LD50 oral rat	2295 mg/kg
LD50 dermal rabbit	> 2000 mg/kg body weight AEPA OPPTS 870.1200
LC50 Inhalation - Rat	1.49 – 2.44 mg/l (OECD 403 method)

Titanium Dioxide (13463-67-7)

LD50 oral rat	> 5000 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	5.09 mg/l/4h

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

LD50 oral rat	3700 mg/kg body weight (OECD 423 method)
LD50 dermal rat	> 3170 mg/kg body weight (OECD 402 method)
LC50 Inhalation - Rat	0.5 mg/l/4h (OECD 403 method)

Silicon Dioxide, Quartz (14808-60-7)

LD50 oral rat	> 22500 mg/kg
---------------	---------------

Dibutylbis(pentane-2,4-dionato-O,O')tin (22673-19-4)

LD50 oral rat	1864 mg/kg body weight (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402 method)
ATE US (oral)	1864 mg/kg body weight

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Stearic acid (57-11-4)	
LD50 oral rat	> 6000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg body weight
LC50 Inhalation - Rat	> 0.1621 mg/l air
LC50 Inhalation - Rat (Vapours)	> 0.1521 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified. The Crystalline Silica is inextricably bound in the chemical matrix of this product and no exposure can occur. Titanium Dioxide is inextricably bound in the chemical matrix of this product and no exposure can occur. Contains no other components or impurities which will influence the classification of the product. ACGIH. IARC. NTP. OSHA

Titanium Dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Silicon Dioxide, Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicity Program (NTP) Status	Known Human Carcinogens

Reproductive toxicity	: May damage the unborn child. Suspected of damaging fertility.
-----------------------	--

Dibutylbis(pentane-2,4-dionato-O,O')tin (22673-19-4)	
NOAEL (animal/male, F0/P)	1.9 – 2.3 mg/kg body weight (OECD 421 method)
NOAEL (animal/female, F0/P)	1.7 – 2.4 mg/kg body weight (OECD 421 method)

STOT-single exposure	: Not classified
----------------------	------------------

Dibutylbis(pentane-2,4-dionato-O,O')tin (22673-19-4)	
STOT-single exposure	Causes damage to organs.

STOT-repeated exposure	: May cause damage to organs (respiratory tract) through prolonged or repeated exposure (Inhalation).
------------------------	---

Trimethoxyvinylsilane (2768-02-7)	
NOAEL (oral,rat,90 days)	62.5 mg/kg body weight (OECD 422 method)

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
NOAEL (oral,rat,90 days)	≥ 500 mg/kg body weight (OECD 422 method)
NOAEL (dermal,rat/rabbit,90 days)	≥ 1545 mg/kg body weight
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Silicon Dioxide, Quartz (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Dibutylbis(pentane-2,4-dionato-O,O')tin (22673-19-4)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Stearic acid (57-11-4)	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight (OECD 422 method)

Aspiration hazard	: Not classified
-------------------	------------------

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Viscosity, kinematic	: No data available
Symptoms/effects	: May cause minor irritation to the respiratory tract and to other mucous membranes. Causes serious eye irritation. May cause slight irritation to the skin. May cause an allergic skin reaction. May cause damage to organs (respiratory system) through prolonged or repeated exposure (inhalation). May damage the unborn child. Suspected of damaging fertility.
Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: May cause slight irritation to the skin. May cause an allergic skin reaction.
Eyes	: Causes serious eye irritation.
Ingestion	: No adverse effects expected under normal conditions of use. Irritation to the digestive tract.
Chronic symptoms	: May cause damage to organs. May damage the unborn child. Suspected of damaging fertility.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: No toxicity data available for product. This product is expected to be harmful to the aquatic environment. Releases to the environment should be avoided.
-------------------	---

Trimethoxyvinylsilane (2768-02-7)	
LC50 - Fish [1]	> 92.2 mg/l <i>Oryzias latipes</i> (Ricefish)
EC50 - Crustacea [1]	≈ 168.7 mg/l <i>Daphnia magna</i> (Water flea)
EC50 72h - Algae [1]	≥ 957 mg/l <i>Desmodesmus subspicatus</i>
LOEC (chronic)	52.4 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC (chronic)	28.1 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
LC50 - Fish [1]	597 mg/l <i>Danio rerio</i> (Zebrafish)
EC50 - Crustacea [1]	81 mg/l <i>Daphnia magna</i> (Water flea)
EC50 72h - Algae [1]	126 mg/l <i>Desmodesmus subspicatus</i>
EC50 72h - Algae [2]	352 mg/l <i>Desmodesmus subspicatus</i>

Titanium Dioxide (13463-67-7)	
LC50 - Fish [1]	> 1000 mg/l <i>Pimephales promelas</i> (Fathead minnow)
EC50 - Crustacea [1]	> 100 mg/l
EC50 - Crustacea [2]	27.8 mg/l <i>Daphnia magna</i> (Water flea)
EC50 72h - Algae [1]	> 100 mg/l <i>Pseudokirchneriella subcapitata</i>
NOEC (chronic)	≥ 2.92 mg/l <i>Daphnia magna</i> (Water flea)

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
LC50 - Fish [1]	5.29 mg/l <i>Oryzias latipes</i> (Ricefish)
EC50 - Crustacea [1]	8.58 mg/l <i>Daphnia magna</i> (Water flea)
EC50 72h - Algae [1]	0.705 mg/l <i>Raphidocelis subcapitata</i>
LOEC (chronic)	0.61 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC (chronic)	0.23 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'

Silicon Dioxide, Quartz (14808-60-7)	
LC50 - Fish [1]	> 10000 mg/l

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Dibutylbis(pentane-2,4-dionato-O,O')tin (22673-19-4)	
LC50 - Fish [1]	> 2 mg/l <i>Oryzias latipes</i> (Ricefish)
EC50 - Crustacea [1]	≈ 0.0036 mg/l <i>Daphnia magna</i> (Water flea)
EC50 72h - Algae [1]	> 2 mg/l <i>Desmodesmus subspicatus</i>
Stearic acid (57-11-4)	
EC50 - Crustacea [1]	> 4.8 mg/l <i>Daphnia magna</i> (Water flea)
EC50 72h - Algae [1]	> 0.9 mg/l <i>Pseudokirchneriella subcapitata</i>
EC50 72h - Algae [2]	11.7 mg/l
LOEC (chronic)	> 0.22 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC (chronic)	> 0.22 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'

12.2. Persistence and degradability

Flex Caulk Can White	
Persistence and degradability	No data available.
Trimethoxyvinylsilane (2768-02-7)	
Persistence and degradability	Not readily biodegradable.
N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
Persistence and degradability	Readily biodegradable.
Titanium Dioxide (13463-67-7)	
Persistence and degradability	Not rapidly degradable
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Persistence and degradability	Not readily biodegradable.
Calcium Carbonate	
Persistence and degradability	Rapidly degradable
Silicon Dioxide, Quartz (14808-60-7)	
Persistence and degradability	Not biodegradable.
Dibutylbis(pentane-2,4-dionato-O,O')tin (22673-19-4)	
Persistence and degradability	Rapidly degradable
Stearic acid (57-11-4)	
Persistence and degradability	Rapidly degradable
Nitrogen (7727-37-9)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Flex Caulk Can White	
Bioaccumulative potential	No bioaccumulation.

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Trimethoxyvinylsilane (2768-02-7)	
Bioconcentration factor (BCF REACH)	≤ 3
Bioaccumulative potential	Low bioaccumulation potential.
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Bioconcentration factor (BCF REACH)	197.1
Bioaccumulative potential	Bioaccumulation is not expected to occur.
Silicon Dioxide, Quartz (14808-60-7)	
Bioaccumulative potential	Not potentially bioaccumulable.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
1950	UN1950	1950	1950
14.2. Proper Shipping Name			
Aerosols	AEROSOLS	AEROSOLS	Aerosols, non-flammable
14.3. Transport hazard class(es)			
2.2	2.2	2.2	2.2
	 Not applicable		
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1950
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

TDG

UN-No. (TDG) : UN1950
Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L
Emergency Response Guide (ERG) Number : 126

IMDG

Special provision (IMDG) : 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP200
Packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

IATA

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provision (IATA) : A98, A145, A167, A802
ERG code (IATA) : 2L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Flex Caulk Can White

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Titanium Dioxide (13463-67-7)

SARA Section 311/312 Hazard Classes

Refer to Section 2 for OSHA Hazard Classification.

15.2. International regulations

CANADA

Trimethoxyvinylsilane (2768-02-7)

Listed on the Canadian DSL (Domestic Substances List)

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Listed on the Canadian DSL (Domestic Substances List)

Titanium Dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Listed on the Canadian DSL (Domestic Substances List)

Calcium Carbonate

Listed on the Canadian NDSL (Non-Domestic Substances List)

Silicon Dioxide, Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Dibutylbis(pentane-2,4-dionato-O,O')tin (22673-19-4)

Listed on the Canadian DSL (Domestic Substances List)

Stearic acid (57-11-4)

Listed on the Canadian DSL (Domestic Substances List)

Nitrogen (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Flex Caulk Can White

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory
Listed on the Canadian DSL (Domestic Substances List)

Flex Caulk Aerosol White

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Titanium Dioxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Silicon Dioxide, Quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations



WARNING:

This product can expose you to Diuron, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Titanium Dioxide(13463-67-7)	U.S. - New Jersey - Right to Know Hazardous Substance List
Calcium Carbonate(1317-65-3)	U.S. - New Jersey - Right to Know Hazardous Substance List
Silicon Dioxide, Quartz(14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List
Nitrogen(7727-37-9)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Revision date : 4/10/2024

Full text of H-phrases

H280	Contains gas under pressure; may explode if heated
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H360	May damage fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

Indication of changes:

new version.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.