





# Safety Data Sheet

安全技术说明书



Nickel Metal Hydride Battery 镍氢电池

Model: 型号:

Ni-MH AA1800mAh 1.2V

Applicant: 申请商: Dongguan FBTech Industrial Co., Ltd 东莞市朗泰通实业有限公司

Report No.: 报告编号:

LTT20221204SDS13

Category: 报告类别:

SDS

广州三帕人在投来服务有限公司 Guangzhou CPUP Certification Technology Service Co., Ltd.

Guangzhou CPUP Certification Technology Service Co., Ltd.

Room C101/C102/C103/C104, No.9, Hengji Road, Yunxing Zhukeng, Shiqiao Street, Panyu District, Guangzhou, Guangdong, China Tel:+86 020-31127037 E-mail:info@cp-up.com http://www.cp-up.com

	Sect	ion 1 - Chemical and Company Identification 第一部合 化学日及本地标识	1
Sample	Name	第一部分-化学品及企业标识 Nickel Metal Hydride Battery	ľ
—————————————————————————————————————		線氢电池	
Model/型号		Ni-MH AA1800mAh 1.2V	770
Ratings/	额定参数	1.2V 1800mAh	
Appli		Dongguan FBTech Industrial Co., Ltd	
申请		东莞市朗泰通实业有限公司	
Applicant address		No.38 Lianhu Road, Laozhongkeng, Sanzhong Village, Qingxi Town,	
申请商地址		Dongguan, Guangdong, China	
		东莞市清溪镇三中老中坑莲湖街 38 号	
Manufacturer		Dongguan FBTech Industrial Co., Ltd	
制造商		东莞市朗泰通实业有限公司	
Manufacturer		No.38 Lianhu Road, Laozhongkeng, Sanzhong Village, Qingxi Town,	
Contact	address	Dongguan, Guangdong, China	6
information	地址	东莞市清溪镇三中老中坑莲湖街 38 号	
制造商联系信息	Tel./应急电话	0769-39021118	
$\bigcirc$	Email/邮箱	2850689053@qq.com	

三帕认证

# Section 2 - Hazards Identification 第二部分-危险性概述

# Hazards Identification: 危险性描述

Not dangerous with normal use. Do not dismantle, open or shred the battery ingredients contained within or their ingredients products could be harmful.

正常使用没有危险,不能拆解、打开或分解电池,里面的材料或成分是有害的。

#### Primary Route (s) of Exposure: 接触途径

inhalation, ingestion, Skin contact and Eye contact.

吸入、食入、皮肤接触、眼睛接触。

#### Potential Health Effects: 潜在健康影响

inhalation: Vapors or mists from a ruptured battery may cause respiratory irritation.

吸入:破裂的电池散发出来的气雾会引起呼吸道刺激。

**Ingestion**: The battery ingredients contained within or their ingredients products can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.

食入: 电池的组成成分或原料可以导致嘴, 食道和胃肠道的严重化学烧伤。

Skin: Skin contact with contents of an open battery can cause severe irritation or burns to the skin.

皮肤:皮肤接触到电池的内部化学材料可能会导致严重的刺激或烧伤皮肤。

#### Eye: Eye contact with contents of an open battery can cause severe irritation or burns to the eye.

眼睛:眼睛接触到电池的内部化学材料可能会导致严重的刺激或烧伤眼睛。



Chemical Name 化学名称	CAS Number CAS 号(化学文摘索引登记号)	Concentration or concentration ranges (%) 浓度或浓度范围(%)
Nickel Hydroxin	12054-48-7	29
Cobaltous Oxide	1307-96-6	5
Steel	7439-89-6	8
Nickel	7440-02-0	10
PVC	9002-86-2	5
Potassium Hydroxide(Liquid)	1310-58-3	3
Sodium Hydroxide	1310-73-2	2
Polypropulene	9003-07-0	3
	7440-02-0	9
	1307-96-6	6
	7439-91-0	4
MH	7440-45-1	6
	7440-10-0	5
	7439-96-5	4
	7429-90-5	1
e: CAS number is Chemical Abstra 意: CAS 号是化学文摘服务注册号。 =Not apply.	ct Service Registry Number.	

Section 4- First Aid Measure 第四部分-急救措施		
Inhalation	Remove source of contamination or move victim to fresh air. Obtain medical advice.	
吸入	移除污染源或者将受害者移至新鲜空气处。寻求医生建议。	
Ingestion 食入	Please rinse mouth thoroughly with water, induce vomiting under the guidance of professional personage. Please seek medical treatment in time. 立即用清水漱口,在专业人士的指导下催吐,速就医。	
Skin contact 皮肤接触	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid. 脱下己污染衣服,用大量的水冲洗至少 15 分钟,速就医。	



Eye contact	Irrigate with flowing water for 15 minutes. If irritation persists, consult a physician.	
眼睛接触	用流动水冲洗 15 分钟,如刺激持续发生,请求助于医生。	

	Section 5- Fire Fighting Measures 第五部分-消防措施
Characteristics of Hazard 危险特性	Toxic fumes, gases or vapors may evolve on burning. 火灾时可释放有害浓烟、气体或者蒸汽。
Hazardous Combustion Products 燃烧产生的危险物品	Carbon monoxide, carbon dioxide, lithium oxide fumes and so on. 一氧化碳,二氧化碳,锂氧化物烟气等。
Fire-extinguishing Methods and Extinguishing Media 灭火方法及灭火剂	Please use water, dry sand and other proper fire extinguishing media. 请使用水,干沙等合适的灭火介质。
Attention in Fire-extinguishing 灭火注意事项	The firemen should put on antigas masks and full fire-fighting suits. 消防人员须佩戴防毒面具、穿全身消防服。

Section 6- Accidental Release Measure 第六部分-泄漏应急处理	
Personal Precautions, protective	Restrict access to area until completion of clean-up.
equipment, and emergency	Do not touch the spilled material. Wear adequate personal protective
procedures	equipment as indicated in Section 8.
· 个人预防措施、防护装备和应急	限制区域,直到完成清理工作。请勿触摸泄漏的材料。穿戴适当的个
程序	人防护设备, 如第8部分所示。
Environmental Precautions	Prevent material from contaminating soil and from entering sewers or
环境保护措施	waterways.
	防止物质污染土壤和进入下水道或水道。
Methods and materials for	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or
Containment	earth. Clean up spills immediately.
方法和材料控制	出于安全,阻止泄漏,可以用干沙或沙土来遏制液体泄露,立即清理
	泄漏。
Methods and materials for	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop
cleaning up	contaminated absorbent into an acceptable waste container. Collect all
清理的方法和材料	contaminated absorbent and dispose of according to directions in Section
	13. Scrub the area with detergent and water; collect all contaminated
	wash water for proper disposal.
	用惰性吸收剂(干沙或沙土)吸收溢出的材料。污染物转移到可吸收废
	物的容器。收集所有受污染的吸收剂和根据第 13 部分的指令处置。
	用洗涤剂和水清洁污染区域,收集所有受污染的洗涤水进行适当处置。

Section 7- Handling and Storage		
	第七部分-操作处置与储存	
Handling	Don't handing the batteries in manner that allows terminals to short circuit. Do not open,	
操作 disassemble, crush or burn battery.		



	不要以让接头短路的方式对电池进行操作。不要打开,分解,挤压或燃烧电池。	
Storage	if the battery is subject to storage for such a long term as more than 3 months, it is recommended	
储存	to recharge the battery periodically.	
	如果电池长期存放超过3个月,建议定期对电池充电。	
	Long period storage: 25±5°C, 60±25%R.H	
	长期存储: 25±5℃,相对湿度 60±25%	
	Do not storage the battery haphazardly in a box or drawer where they may short-circuit each	
	other or be short-circuited by other metal objects.	
	不要将电池随意丢在盒子或抽屉里,以免电池之间或电池与其他金属物质发生短路。	
	Keep out of reach of children.	
	储存在小孩接触不到的地方。	
	Do not expose the battery to heat or fire. Avoid storage in direct sunlight.	
	不要将电池暴露在火源和热源附近,避免在阳光直射下存储。	
	Do not store together with oxidizing and acidic materials.	
	不要与氧化和酸性物质存储在一起。	

Section 8 - Exposure Controls/Personal Protection 第八部分-接触控制和个体防护		
Engineering Controls 工程控制	No engineering controls are required for handling batteries that have not been damaged. Personal protective equipments for damaged batteries should include chemical resistant gloves and safety glasses. 操作未破损的电池,没有工程控制要求。对于破损的电池,个人防护用品应包括 化学品防护手套和安全眼镜。	
Personal Protective Equipment 个人防护设备	Respiratory Protection: in case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use. Not necessary under conditions of normal use. of protection is not necessary under conditions of normal use. Not necessary under conditions of normal use. of protective flow and the protection of the protection of the protective Clothing or Equipment: Not necessary under conditions of normal use. protective Clothing or Equipment: Not necessary under conditions of normal use. The protective Clothing or Equipment: Not necessary under conditions of normal use. protective Clothing or Equipment: Not necessary under conditions of normal use. Personal Protection is recommended for venting battery: Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields. 当电池排气阀打开时,应做好个人防护。呼吸防护,防护手套,防护服装和有护 边的安全玻璃罩都是要准备的。	

# Section 9- Physical and Chemical Properties 第九部分-理化特性

**Appearance**: Green **外观颜色**: 绿色



Report No.:	LTT20221204SDS13
-------------	------------------

Physical state: Solid		
<b>物理状态:</b> 固体		~
Form: Cylindrical		and the second
<b>形状:</b> 圆柱形		
Odor: Odorless	Ô	
<b>气味:</b> 无气味		
Solubility: Partial soluble in water		
溶解度: 部分溶于水		

Section 10 - Stability and Reactivity		
第十部分-稳定性和反应性		
Stability	Stable under normal temperatures and pressures.	
稳定性	常温常压下稳定。	
Conditions to Avoid	Heat above 70°C or Incinerate, Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions.	
应避免的条件	加热 70°C 以上或焚烧、变形、毁坏、粉碎、拆卸、过充电、短路, 长时间暴露在潮湿的条件下。	
Hazardous Decomposition Products 危害分解物	Toxic Fumes, and may form peroxides. 有毒烟雾,并可能形成过氧化物。	
Possibility of Hazardous Reaction	If leaked, forbidden to contact with strong oxidizers ,mineral acids ,strong alkalis, halogenated hydrocarbons.	
Reaction 危险反应的可能性	如果发生泄露,避免与强氧化剂,无机酸,强碱,卤代烃接触。	

	如不及工把路, 题光马庶氧化剂, 光机散, 屈赖, 固代杜按屈。				
Section 11 - Toxicological Information					
	第十一部分-毒理学信息				
Irritation 刺激	In the event of exposure to internal contents, vapor fumes may be very				
	irritating to the eyes and skin.				
	内部物质暴露的情况下,蒸汽烟雾可能对眼睛和皮肤产生刺激性。				
Sensitization	Not applicable.				
致敏 幻觉 是	不适用				
Reproductive Toxicity	Not applicable.				
再生毒性	不适用				
Toxicologically Synergistic	Not applicable.				
Materials					
协同材料毒理学	不适用				

Section 12-Ecological Information		
第十二部分-生态学信息		
General note 通用信息	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.	
	不允许未稀释或大量的产品到达地下水、水道或污水系统。	



Anticipated behavior of a chemical product in environment/possible environmental impact/ ecotoxicity 化学产品在环境/可能的环境预 期的行 为的一种生态毒性	Not applicable. 不适用	277>
Mobility in soil 土壤中移动性	Not applicable. 不适用	
Persistence and Degradability 持久性和降解性	Not applicable. 不适用	

Section 13 - Disposal Considerations 第十三部分-废弃处置				
Waste Treatment 废弃处置方法	regulations.			
	建议遵照国家和地方法规处置或再利用。			
	Deserted batteries couldn't be treated as ordinary trash. Couldn't be thrown into fire or			
Attention for Waste	placed in high temperature. Couldn't be dissected, pierced, crushed or treated similarly.			
Treatment	ment Best way is recycling.			
废弃注意事项	度电池不能被当做普通垃圾。不能扔进火中或置于高温下。不能解体, 刺穿,破碎或类似			
	的处理。最好的办法是回收利用。			
	/2)			

Section 14 - Transport Information				
· · · · · · · · · · · · · · · · · · ·				
The battery shall be protected so as to prevent short circuits. This includes protection against contact w	/ith			
conductive materials within the same packaging that could lead to short circuit;				
该电池必须做好防短路保护。包括防止与同一封装内的导电材料接触可能导致的短路。				
The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking.				
包装应足以避免在运输,处理和堆放期间的机械损坏。				
The package must be handled with care and that a flammability hazard exists if the package is damaged. 包装	铋			
须小心处理,如果包装损坏,存在易燃危险。				
With regard to transport, the following regulations are cited and considered:				
关于运输,引用和考虑了以下法规:				
-The international Civil Aviation Organization (ICAO) Technical Instructions.				
-国际民用航空组织(ICAO)技术细则。				
-The international Air transport Association (IATA) Dangerous Goods Regulations.				
-国际航空运输协会(IATA)危险物品规则。				
UN Proper shipping name/Description (technical name): Batteries, Nickel-metal Hydride				
UN 合适的运输名称/描述(技术名称): 电池, 镍氢				
UN number: N/A				
UN 编号: N/A				
UN Classification (Transport hazard class): N/A				
UN 分类(运输危险类别):不适用				
UN Packing Group: N/A				



UN 包装类别:不适用 The battery can be shipped by air in according to special provision A199 of the 2023 IATA Dangerous Goods regulations 64<sup>th</sup> Edition. 该电池可以根据 2023 年 IATA 危险物品规则第 64 版特殊条款 A199 运输。 -The international Maritime Dangerous Goods (IMDG) Code. -国际海运危险货物(IMDG)规则。 UN number: UN3496 (100kg gross mass or more) or N/A (less than100kg gross mass); UN 编号: UN3496(总质量大于等于 100Kg)或不适用(总质量小于 100Kg) UN Proper shipping name/Description (technical name): Batteries, Nickel-metal Hydride UN 合适的运输名称/描述(技术名称): 电池, 镍氢 UN Classification (Transport hazard class): Class 9(100kg gross mass or more) or Not applicable (less than100kg gross mass); UN 分类(运输危险类别): 9 类危险品(总质量大于等于 100Kg)或不适用(总质量小于 100Kg) UN Packing Group: Not applicable UN 包装类别:不适用 EmS No.: F-A, S-I Ems 编号: F-A, S-I When loaded in a cargo transport unit in a total quantity of less than100kg gross mass, The battery is not restricted according to IMO IMDG Code (inc. Amendment 40-20) special provision 963. 当装载货物总质量小于 100kg, 海运按照国际海事组织《国际海运危险货物规则》(40-20 版) 特殊条款 963 可按 普通货物条件办理。

# Section 15 - Regulatory Information 第十五部分-法规信息

The international Civil Aviation Organization (ICAO) Technical Instructions.

国际民用航空组织(ICAO)技术细则。

The international Air transport Association (IATA) Dangerous Goods Regulations.

国际航空运输协会(IATA)危险物品规则。

The international Maritime Dangerous Goods (IMDG) Code.

国际海运危险货物(IMDG)规则。

		Section 16 - Additional Information 第十六部分-附加信息
Compiler 编制人:	Ailen Feng	
Reviewer 审核人:	Tracy Chen	
Approver 批准人:	Leothi	
Issue Date 签发日期: 2022.12.12		
Effective date 生效日期: 2023.01.01		



### Compile unit 编制单位:

Guangzhou CPUP Certification Technology Service Co., Ltd.

广州三帕认证技术服务有限公司

Room C101/C102/C103/C104, No.9, Hengji Road, Yunxing Zhukeng, Shiqiao Street, Panyu District, Guangzhou, Guangdong, China

广州市番禺区市桥街云星珠坑村横基路9号C101、C102、C103、C104室

Tel./电话: 0086-20-31127037 Web/网址: www.cp-up.com Email/邮箱: info@cp-up.com

# Other Information 其他信息:

The information above is believed to be accurate and represents the best information currently available to us. However, we makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

在我们看来上面的信息是准确的,这是我们目前能提供的最佳的信息。但是,对于这些信息,我们不对商品的性能 做任何明示的或者暗示的保证,我们也不对使用这些信息造成的后果担负任何责任。用户应当自己调查研究后决定 这些信息是否适用于他们的特定用途。尽管在该文档里提出了合理的预警,但是这仅仅只是给您做参考、考量和调 查。这份安全技术说明书提供了安全处理和使用该产品的指南,但是它没有,也不能对所有可能发生的情景提出建 议,所以您需要根据您对该产品的特定使用情况来决定是否需要其他的预防措施。

> --End of report----报告结束--



