

02-XP-SLR

COMPACT THERMOPLASTIC EXIT SIGN

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- Aesthetically pleasing, curved face, rounded corner design.
- EZ snap-out chevron directional indicators.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 1.2V Long life, maintenance-free, rechargeable NiCd battery.
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LED.

MOUNTING

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

CODE COMPLIANCE

- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.


WARRANTY

- Five year warranty on all electronics and housing. Battery prorated for five years.

OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes. Universal 120-277 voltage.
- Custom: Signs available with requested 'special' wording.
- USA: Substantial transformation assembly in the U.S. complies with "Assembled in USA" under the Buy American Act.

PROJECT
TYPE
CATALOG #



STANDARD



OPTIONAL



PRODUCT PARAMETERS

MODEL	LETTER COLOR	HOUSING COLOR	BATTERY	SELECT	OPTIONS
02-XP-SLR	R = Red G = Green RG = Red/Green	W = White B = Black	Blank = AC Only EM = Battery Backup	SLR = Slim Line Round	SDT = Self-Diagnostic Custom = Custom wording USA = Assembled in USA



PROJECT
TYPE
CATALOG #

02-XP-SLR

COMPACT THERMOPLASTIC EXIT SIGN

ELECTRICAL INFORMATION

CATALOG NUMBER	INPUT WATTS (W) 120V	INPUT WATTS (W) 227V	INPUT AMPS (A) 120V	INPUT AMPS (A) 277V
02-XP-SLR-RED/GREEN EM	1.0	1.0	0.1	0.1
02-XP-SLR-RED SDT	2.5	2.5	0.05	0.05
02-XP-SLR-GREEN SDT	2.7	2.7	0.05	0.05