

Dehumidifiers

LGR 2800i

High-temp dehumidification for peak efficiency. This i-Series unit automatically adjusts operation for maximum efficiency in low RH or high temperature environments. Features the new [Command Hub](#), compatible with the new Command Center App. Take advantage of Bluetooth and WiFi connectivity to control the dehu and view jobsite conditions remotely. Available in early 2023 in the [Apple Store](#) and [Google Play Store](#).

Features

- NEW! Command Hub touchscreen controller displays real-time temp, RH, grain depression and drying progress trends at a glance. Controller integration product for existing i-Series dehumidifiers also available. [Learn more](#).
- Fast and convenient access to humidistat, job hours, maintenance reminders and more.
- Automatic high temperature mode – no manual adjustments required.
- Legendary Dri-Eaz rotomolded housing resists dents and scratches – and is easy to keep looking new.
- Automatic restart after outage when power is restored.

Specifications

- **Water removal AHAM (80°F/60%RH):** 130 pts. | 61.5 L / day
- **Water removal max. (90°F/90%RH):** 200 pts. | 94.6 L / day
- **Max. Process Air :** 400 CFM | 679.7 CMH Automatic variable speed for optimized performance.
- **Dimensions (W × H × D):** 24 × 40.5 × 23 in. | 61 × 103 × 58 cm
- **Use weight:** 156 lbs. | 70.8 kg
- **Amps:** 8.0A
- **Volts:** 115V
- **Frequency:** 60Hz
- **Air filter:** 4-PRO filter
- **Hose:** 40 ft. | 12.2 m
- **Power cord:** 25 ft. | 7.6 m detachable
- **Housing:** Rotomolded polyethylene
- **Safety:** ETL listed to UL/cUL 474 and CSA 22.2 no. 92
- **Xactimate:** WTRDHM>>XL

Sizes ▪ Options

- 110128 (F410): One unit