



Protect It! Surge Protector with 6 Rotatable Outlets, Direct-Plug In, 1500 Joules

MODEL NUMBER: SWIVEL6











Highlights

- 6 rotatable outlets
- Direct plug-in design
- 1500 joule rating
- Diagnostic LEDs

Package Includes

- SWIVEL6 Surge Suppressor
- Instruction manual with warranty information

Description

The SWIVEL6 offers reliable surge and line noise protection. Premium features include a compact, direct plug-in design for easy portability, six rotatable outlets for easier plug connection and removal and 1500 joules of surge absorption protection. Diagnostic LEDs alert you to potential wiring or protection faults before connected equipment is damaged. \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- 6 rotatable outlets allow for easier plug connection and removal
- 1500 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 2 diagnostic LEDs alert user to protection and grounding status
- High-impact plastic housing (black) stands up to the most demanding environments
- Direct plug-in design converts two outlets into six by pluggin into any wall outlet
- \$20,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required

Specifications

OVERVIEW	
UPC Code	037332138231



OUTPUT Frequency Compatibility	60 Hz	
Output Receptacles	(6) 5-15R	
Circuit Breaker (amps)	15	
Outlet Orientation	Rotatable	
Right-Angle Outlets	No	
	1.7	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Connection Type	NEMA 5-15P	
Input Cord Length (ft.)	0	
Input Cord Length (m)	0.00	
Input Cord Length Details	Direct plug-in	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	60000	
Right-Angle Plug	No	
USER INTERFACE, ALERTS & CON	TROLS	
Diagnostic LED(s)	Yes	
Diagnostic LED Details	Built-in LEDs confirm suppressor "protected" (green) and "grounded" (red) status	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	1500	
AC Suppression Response Time	<1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping Voltage (RMS)	150	
UL1449 Let Through Rating	400, 500, 500	
EMI / RFI Filtering	Up to 20 dB	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		





Shipping Dimensions (hwd / in.)	7.50 x 2.25 x 9.10	
Shipping Dimensions (hwd / cm)	19.05 x 5.72 x 23.11	
Shipping Weight (lbs.)	0.75	
Shipping Weight (kg)	0.34	
Unit Dimensions (hwd / in.)	6.25 x 4 x 2.25	
Unit Dimensions (hwd / cm)	15.88 x 10.16 x 5.72	
Unit Weight (lbs.)	0.6	
Unit Weight (kg)	0.27	
Material of Construction	Plastic	
Housing Color	Black	
Receptacle Color	Black	
Outlets Measurement (Center to Center)	29mm	
Anti-Microbial Protected	No	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3RD EDITION	
cUL / CSA (Canada)	cUL	
Approvals	RoHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$20,000 Ultimate Lifetime Insurance	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies