

### **CODE NUMBER**

33153026

### **DESCRIPTION**

IoT - SC Argus<sup>™</sup> Pro, 8" Trim Plate, Box Transformer Power Supply, Below Deck Manual Mixing Valve, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, SC Argus<sup>™</sup> Pro Compatible, Optima® Hardwired-Powered Deck-Mounted Low Body IoT.

### **DETAILS**

Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)Spray Type: Multi-Laminar (MLM)

Sensor Type: Infrared (IR)
Mounting Type: Single Hole
Trim Plate: 8" (203mm) (8)

• Power Supply: Box Transformer (BOX)

• Temperature Mixer: Below Deck Manual Mixing Valve (BDM)

• Finish: Polished Chrome (CP)

Factory Default Timeout: 30 secondsFactory Default Gallons per Cycle: 0.25

IoT: SC Argus<sup>™</sup> Pro Compatible

# **FEATURES**

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- On-demand or Metered activation
- Self-adapting Sensor

# **IOT Smart Capabilities**

- Compatible with Sloan's SC Argus Pro smart restroom system
- Automatically sends faucet data to SC Argus Pro system
- Provides detailed product information, image, model, total activations, total operating hours, location room
- Remote access to Water usage, daily activations, operating status and battery strength reporting
- Remote setting adjustments via SC Argus Pro
- Remote hygienic line flush settings and changes
- Notes area to track maintenance details and location
- Requires subscription to SC Argus Pro SaaS

# **ELECTRICAL SPECIFICATIONS**

- Sensor Range: 4"-5" (102-127mm)
- Timeout Adjustment Settings: 30s

## **POWER SUPPLY OPTIONS**


• 24VAC Box Transformer (included with BOX models), 0345370PK

## **VIDEOS**

Sloan Optima Below Deck Faucet

PVD Special Finishes





# **COMPLIANCES & CERTIFICATIONS**





















(ADA Compliant, ASME A112.18.1 Compliant, ASSE 1070, CalGreen Compliant, CEC Compliant, cUPC Certified, UPC Certified, UPC Low Lead Compliant, cUPC Low Lead Compliant, EPD, FCC Certified, GPC 0.25 or less, HPD, NYC604.4, Proposition 65, TAS, WELL Building Standard)

# RECOMMENDED SPECIFICATION

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of settings wirelessly via SC Argus Pro software-as-a-service

## **NOTES**

All information contained within this document subject to

**Sloan 10500 Seymour Ave, Franklin Park, IL 60131** Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com









SC Argus™ Pro

## **DOWNLOADS**

- Optima Smart Faucet Below Deck Installation Instructions
- Faucet Spray Heads Repair and Maintenance Guide
- Optima EBF-415 / ETF-410 Repair & Maintenance Guide and Parts Breakdown
- Additional Downloads

# **ROUGH-IN**


change without notice.

Looking for other variations of the ETF-410 SMT product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet. Find a compatible sink for this faucet.

#### WARRANTY

View Warranty Information



Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com