

CODE NUMBER

3325502

DESCRIPTION

GEM Adapter, Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Battery, Exposed Sensor Urinal/Water Closet Retrofit Flushometer.

DETAILS

Finish: Polished Chrome (CP)Power Type: Battery ()Battery Life: 3 years

Valve: Diaphragm/Piston
Fixture Type: Urinal/Water Closet
Fixture Connection: Top Spud
Adapter: GEM Adapter (GEM)

FEATURES

- Non-Hold-Open True Mechanical Override Full Flush Button
- Four (4) Size C batteries included
- 72-Hour Sentinel Flush
- "Low Battery" Flashing LED
- "User in View" Flashing LED
- No External Volume Adjustment to Ensure Water Conservation



COMPLIANCES & CERTIFICATIONS



BREEAM



GREE

(ADA Compliant, BREEAM Water Credit, cUPC Certified, Green Globes Water Credit)

ELECTRICAL SPECIFICATIONS

• Arming Delay: 1-3 seconds

• Battery Life: 3 years

 Control Circuit: 6 VDC Input/72 Hour Sentinel Flush/Solid State

State

• Sensor Range: 22"-42" (559-1,067mm)

VALVE OPERATING PRESSURE (FLOWING)

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- EBV-500/550-A Installation Instructions
- EBV500/EBV550 Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EBV500A product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer. Find a compatible water closet for this flushometer.

Battery life varies according to actual usage and restroom conditions.



ROUGH-IN

