

EVERPURE® CLARIS LARGE FILTER CARTRIDGE

ADJUSTABLE ION-SELECTIVE FILTERS TO TAILOR CARBONATE HARDNESS LEVELS IN POTABLE WATER

Claris Large Filter Cartridge: EV4339-12



APPLICATIONS

Coffee
Espresso
Hot drink vending
Combi steamers

Self-cooking systems
Steam cookers and ovens
Brewed iced tea

FEATURES • BENEFITS

Five-stage filtration process

- Prefiltration
- Carbonate hardness adjustment
- Fine filtration
- Highly efficient carbon block
- Solid membrane filter

NSF® Certified under NSF/ANSI Standard 42

Removes harmful contaminants and unpleasant odors and tastes

Removes particles down to five (5) micron for highest equipment protection

Operation in vertical or horizontal position

INSTALLATION TIPS

The system can be operated freestanding, lying horizontally or mounted vertically

If mounting vertically to a wall, securely connect the mounting bracket to the wall using suitable screws

Water pressure at the filter system inlet must not exceed 116 psi (8 bar). A pressure reducer valve must be installed on the water supply side of the filter system if the inlet pressure exceeds 116 psi (8 bar)

Shutoff valve must be installed upstream of the filter

Refer to Installation, Operation & Maintenance Manual for cartridge flushing and startup

OPERATION TIPS

Change Claris cartridges when its pre-calculated water volume has been reached or at least once per year

Change cartridges when capacity is reached

Always flush the filter cartridge at time of installation and cartridge change

Do not use hardness test strips to check for hardness reduction. Please use Titration kit to check for hardness reduction


SIZING

Service Flow Rate: Maximum 1.0 gpm (4 Lpm)

Rated Capacity: 1,100 gallons (4,163 L) for espresso and 1,320 gallons (4,996 L) for OCS/coffee. This capacity is based on influent water hardness of 180 ppm with standard bypass settings. For steam applications and other hardness levels consult installation and operations guide capacity and bypass settings charts

EVERPURE® CLARIS LARGE FILTER CARTRIDGE

EV4339-12



SPECIFICATIONS

Overall Dimensions

14.18" L x 5.35" dia. (36.0 cm x 13.6 cm)

Service Flow Rate

Maximum 1.0 gpm (4 Lpm)

Rated Capacity

1,100 gallons (4,163 L) for espresso and
1,320 gallons (4,996 L) for OCS/coffee.

This capacity is based on influent water hardness of 180 ppm with standard bypass settings. For steam applications and other hardness levels consult installation and operations guide capacity and bypass settings charts.

Pressure Requirements

29 - 116 psi (2 - 8 bar), non-shock

Temperature

39 - 86°F (4 - 30°C)

Electrical Connection

None required



System Tested and Certified by NSF
International against NSF/ANSI
Standard 42 for the reduction of:

Standard No. 42 Aesthetic Effects
Chemical Unit
Taste and Odor Reduction
Chlorine Reduction

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

WARRANTY

Everpure Claris water treatment systems by Pentair® (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.



FILTRATION & PROCESSING SOLUTIONS

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • WWW.EVERPURE.COM
800.942.1153 MAIN (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO AUSTRALIA / NEW ZEALAND, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC, 3175, AUSTRALIA
1300.576.190 TEL • AU.EVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO CHINA, 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA
86.21.3211.4588 TEL • 86.21.3211.4580 FAX • CHINA.WATER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO INDIA, GREEN BOULEVARD, B-9/A, 7TH FLOOR - TOWER B SECTOR 62, NOIDA - 201301
91.120.419.9444 TEL • 91.120.419.9400 FAX • INDIACUSTOMER@PENTAIR.COM EMAIL

EVERPURE-SHURFLO EUROPE, PENTAIR WATER BELGIUM BVBA, INDUSTRIEPARK WOLFSTEE, TOEKOMSTLAAN, 30 B-2200 HERENTALS, BELGIUM
+32.(0).14.283.500 TEL • +32.(0).14.283.505 FAX • SALES@EVERPURE-EUROPE.COM EMAIL

EVERPURE-SHURFLO JAPAN INC., HASHIMOTO MN BLDG. 7F, 3-25-1 HASHIMOTO, MIDORI-KU, SAGAMIHARA-SHI KANAGAWA 252-0143, JAPAN
81.(0)42.775.3011 TEL • 81.(0)42.775.3015 FAX • INFO@EVERPURE.CO.JP EMAIL

EVERPURE-SHURFLO SOUTHEAST ASIA, 390 HAVELOCK ROAD, #04-01, KING'S CENTRE, SINGAPORE 169662
65.6795.2213 TEL • FAX: 65.6795.2219 FAX • CSEVERPURE@PENTAIR.COM EMAIL

All Pentair trademarks and logos are owned by Pentair, Inc. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.