

39513

Detail Brush with Scraping Edge, 5.9" Stiff, Blue



A very effective detail brush. The solid scraping edge is suitable to loosen very stubborn dirt from surfaces. The flat hand grip offers a good support and control in your hand for a variety of cleaning tasks.

Extra force can be applied during scrubbing by pressing your forefinger down on the brush head during cleaning.

Technical Data

Item Number	39513
Visible bristle length	0.8 "
Material	Polypropylene Polyester
Complies with (EC) 1935/2004 on food contact materials ¹	Yes
Produced according to EU Regulation 2023/2006/EC of Good Manufacturing Practice	Yes
FDA-compliant raw material (CFR 21)	Yes
Complies with UK 2019 No. 704 on food contact materials	Yes
Meets the REACH Regulation (EC) No. 1907/2006	Yes
California Proposition 65 Compliant	Yes
Use of phthalates and bisphenol A	No
Is Halal and Kosher compliant	Yes
Design Registration No.	EU 008554125-0002, UK 6139372
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x 180-200 cm)	4600 Pcs.
Quantity Per Layer (Pallet)	230 Pcs.
Length	5.9 "
Width	1.1 "
Height	3.5 "
Net Weight	0.0551 lbs
Weight bag (Recycling Symbol "4" Low Density Polyethylene (LDPE))	0.01 lbs
Weight cardboard (Recycling symbol "20" PAP)	0.02 lbs
Tare Total	0.02 lbs
Gross Weight	0.0789 lbs
Cubic Feet	0.0129 ft3
Recommended sterilisation temperature (Autoclave)	249.8 °F
Max. cleaning temperature (Dishwasher)	199.4 °F
Max usage temperature (food contact)	176 °F
Max usage temperature (non food contact)	212 °F
Min. usage temperature	-4 °F
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	10.5 pH
GTIN-13 Number	5705022030091
GTIN-14 Number (Box quantity)	15705028030108
Customs Tariff No.	96039099

New equipment should be cleaned, disinfected, sterilized, and any labels removed, as appropriate to its intended use, e.g. high risk vs. low risk food production areas, general hospital areas vs. intensive care units, before use.

1. See Declaration of Compliance for further details on food contact
3. Do not store the product below 32 °Fahrenheit.