

SPFZ25



17" x 21.25" x 14.25" (H x W x D)

Portable 12V/24V vaccine freezer designed to operate between -20 and -27°C with AC adapter included

Highlights:

Portable 12V/24V compressor-powered freezer for the safe storage of vaccines, pharmaceuticals, and other materials

Includes connections for both a 12/24V auxiliary power outlet and an adapter/cord for 110V outlets

Low temperature performance can run between -20 and -27°C

Product Features:

| | |
|----------------------------|---|
| Portable freezer | Designed to maintain the integrity of the cold chain when transporting sensitive materials |
| 12V/24V DC hookup | Cord included to plug the unit into a vehicle's auxiliary power outlet or a 24V battery |
| AC Adapter included | We provide an AC adapter for users to plug the unit into a standard 110-120V wall socket for stationary use |
| Low temperature operation | Temperature range from -20 to -27°C for a variety of storage applications, including certain vaccines |
| Hammered aluminum interior | Durable construction to hold up to everyday use |
| Digital thermostat | Easy temperature control with electronic buttons and an external thermometer readout |
| Side handles | Sturdy handles are easy to grab for comfortable lifting and carrying |
| Compressor-powered cooling | Reliable performance with fast temperature recovery |
| 100% CFC free | Environmentally friendly design does not contain ozone-damaging chemicals |

SPFZ25 Specifications:

| Overview | |
|------------------------|--------------------|
| Height of Cabinet | 17.0" (43 cm) |
| Width | 21.25" (54 cm) |
| Depth | 14.25" (36 cm) |
| Capacity | 0.88 cu.ft. (25 L) |
| Defrost Type | Manual |
| Door | White |
| Cabinet | Blue |
| Amps | 7.0 |
| Weight | 30.0 lbs. (14 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| UPC | 761101084169 |
| Freezer | |
| Door Swing | Lift-Up |
| Interior Height | 12.0" (30 cm) |
| Interior Width | 13.0" (33 cm) |
| Interior Depth | 9.75" (25 cm) |
| Thermostat Type | Digital |
| Refrigerant Type | R290 |
| Refrigerant Amount | 0.81 oz. |
| High Side PSI | 206.0 |
| Low Side PSI | 15.0 |
| Compressor Step Height | 7.25" (18 cm) |
| Compressor Step Width | 2.5" (6 cm) |
| Compressor Step Depth | 9.75" (25 cm) |
| Temperature Range | -20 to -27°C |
| Sound Level | 44.7 dB |

