

DeWALT® DUCT TAPE

ULTRA-TOUGH THICK DUCT TAPE

DESCRIPTION

Strong, durable duct tape designed for the most demanding applications. Strong woven cloth/poly backing provides greater strength than typical duct tape. Ultra-strong adhesive provides superior adhesion to both smooth and rough surfaces. Superior construction provides ultimate performance in most demanding environments.

PRODUCT APPLICATION

Ultimate performance on wood, stone, brick, film, stucco and metals. Excellent for construction, automotive, marine and industrial applications – as well as those demanding jobs around the house.

GOVERNMENT/CODE CONFORMANCE

Tested in accordance with UL723/
ASTM E-84.



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/22

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing	PE Film
Adhesive	Natural Rubber/Resin
Reinforcement	PET Cloth
Adhesion to Steel (oz/in of width) PSTC-101	85 (23.2 N/25mm)
Tensile Strength (lbs/in of width) PSTC-131	48 (210.5 N/25mm)
Elongation (% at break) PSTC-131	26
Total Thickness (mils) PSTC-133	17.0 (0.432mm)
Color	Black
Temperature Resistance	+32°F ~ +200°F (+0°C ~ +93°C)

**DEWALT**