

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Spec-Bar® Recessed Workboard, model ______. Heavy gauge type 304 stainless steel body, legs, leg channels and cross rails. Stainless steel removable perforated insert and shelf. Stainless steel adjustable bullet feet.



19" (483mm)
recessed workboard with
single speed rail profile



19" (483mm) recessed workboard with double speed rail profile



24" (610mm) recessed workboard with no speed rail profile

EAGLE GROUP

www.eaglegrp.com



24" (610mm) recessed workboard with single speed rail profile

Item No.:	
Project No.:	
S.I.S. No.:	

Spec-Bar® Recessed Workboards

MODELS:

□ <i>RDBSR12-19</i>	□ <i>RDB12-24</i>
□ <i>RDBSR18-19</i>	□ <i>RDB18-24</i>
<i>□RDBSR24-19</i>	□ <i>RDB24-24</i>
□ <i>RDBSR30-19</i>	□ <i>RDB30-24</i>
<i>□RDBSR36-19</i>	□ <i>RDB36-24</i>
<i>□RDBDR12-19</i>	□ RDBSR12-24
<i>□RDBDR18-19</i>	□ RDBSR18-24
<i>□RDBDR24-19</i>	□ RDBSR24-24
<i>□RDBDR30-19</i>	□RDBSR30-24
□ <i>RDBDR36-19</i>	□RDBSR36-24

Design and Construction Features

- Backsplash, sides, front panel, drain pan and perforated insert are 20 gauge type 304 stainless steel.
- Leg channels, legs and crossbracing are 16 gauge type 304 stainless steel.
- Legs are 1%" (41mm) diameter, with stainless steel adjustable bullet feet.
- Designed to align with single or double speed rails installed on adjoining equipment.
- Removable insert and shelf made of perforated stainless steel.
- 1½" (38mm) I.P.S. threaded drain with nut and washer.

Certifications / Approvals







Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

For custom configuration or fabrication needs, contact our **SpecFAB® Division**. Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: specfab@eaglegrp.com


EG40.28 Rev. 04/11



Item No.: .	
Project No.: .	
S.I.S. No.: .	

Spec-Bar® Recessed Workboards


19" (483mm) Recessed Workboards with Single Speed Rail Profile – 24" (610mm) overall width



Aligns with Spec-Bar® series 19" (483mm) equipment with 5" (127mm) single speed rail.

	width		length		weight	
model #	in.	mm	in.	mm	lbs.	kg
RDBSR12-19	24"	610	12″	305	25	11.3
RDBSR18-19	24"	610	18″	457	30	13.6
RDBSR24-19	24"	610	24"	610	35	15.9
RDBSR30-19	24"	610	30"	762	40	18.1
RDBSR36-19	24"	610	36″	914	45	20.4

24" (610mm) Recessed Workboards with No Speed Rail Profile – 24" (610mm) overall width



Aligns with Spec-Bar® series 24" (610mm) equipment with no speed rail.

	wi	dth	length		weight	
model #	in. mm		in.	in. mm		kg
RDB12-24	24"	610	12″	305	25	11.3
RDB18-24	24"	610	18″	457	30	13.6
RDB24-24	24"	610	24"	610	35	15.9
RDB30-24	24"	610	30"	762	40	18.1
RDB36-24	24"	610	36″	914	45	20.4

EAGLE GROUP


100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100


19" (483mm) Recessed Workboards with Double Speed Rail Profile – 29" (737mm) overall width



Aligns with Spec-Bar[®] series 19" (483mm) equipment with 10" (254mm) double speed rail.

. o (=0) a dabid op dda .a								
	width		length		weight			
model #	in.	mm	in.	mm	lbs.	kg		
RDBDR12-19	29"	737	12″	305	37	16.8		
RDBDR18-19	29"	737	18″	457	42	19.1		
RDBDR24-19	29"	737	24"	610	49	22.2		
RDBDR30-19	29"	737	30"	762	56	25.4		
RDBDR36-19	29"	737	36″	914	61	27.7		

24" (610mm) Recessed Workboards with Single Speed Rail Profile – 29" (737mm) overall width



Aligns with Spec-Bar® series 24" (610mm) equipment with 5" (127mm) single speed rail.

	width		length		weight	
model #	in.	mm	in.	mm	lbs. kg	
RDBSR12-24	29"	737	12″	305	37 16.8	
RDBSR18-24	29"	737	18″	457	42 19.1	
RDBSR24-24	29"	737	24"	610	49 22.2	
RDBSR30-24	29"	737	30"	762	56 25.4	
RDBSR36-24	29"	737	36″	914	61 27.7	

Printed in U.S.A. ©2011 by Eagle Group

Rev. 04/11