

Model 630ADGP



Single Door, Upright, Indoor Ice Merchandiser

Model	Dimensions D x W x H	Volts / Hertz / Phase	Amps	Unit H.P.	Refrigerant	Capacity (Cu. Ft.)	Approx. Shipping Weight (lbs.)
630ADGP	Ext. 35" x 62" x 79" Int. 31" x 58" x 59"	115V / 60HZ / 1PH	6.75 amps / 15-amp circuit	1/3	R-290	61	475

Agency Listings

- ETL Listed in accordance to UL 60335-1-89 and UL 60335-2-89 Standard - 2nd Edition

Connections

- Electrical connection: Heavy Duty 12-Gauge 10-Foot Cord with plug
- Condensation Plumbing Connection: 1/2" I.D. Plastic Tube

Optional Features

- 24" LED Light
- Bright Aluminum Diamond Plate Kick Plate
- Door Opening Ice Breaker Bar
- 4" Casters with 1/4" Aluminum Angle Perimeter Frame
- TX Valve Metering Device
- ETL Listed in accordance to NSF7 Standard
- Shelves

Standard Features

- Merchandiser designed to hold product between 10°F to 20°F
- 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- Triple Pane Glass Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- Top Mounted Refrigeration System with Low Global Warming Potential
- Aluminum Fin/Copper Tube Evaporator with Capillary Tube
- Environmentally-friendly, nonflammable, foamed-in-place insulation that provides exceptional energy efficiency.
- Electronic Control System Gives Service Friendly Fault Codes
- Electric Automatic Defrost (AD) System
- Electric Condensation Pan mounts to rear of merchandiser
- Floor Racks
- Solid Injection Molded Feet