

AQUVERSE



P.O.U.
WATER
COOLERS

INNOVATIVE WATER PERFORMANCE



DRINKING WATER
COOLER
LISTED
36NK

7 PH

7 PH SPECIFICATIONS

AQUVERSE

Point of use water cooler

Model	7 PH
Cold Water	1.4 GAL OF 50 / HR (5.5L OF 10°C)
Hot Water	1.8 GAL OF 185 / HR (7.0 OF 85 5°C)
Dimensions	11.4" (290MM) X 14.4" D (365MM) X 44.9" H (1140MM)
Shipping Weight	55 LBS (25KG)
Room Temp. Water	NON

*Specifications are subject to change without notice.

CABINET

Top and front panels are molded of ABS plastic and side panels are made of electric zinc coated steel with high polymer polyester resin.

REFRIGERATION UNIT

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No Lubricant needed. Refrigerant is controlled by accurately calibrated cappillary tube.

DRIP TRAY

Concealed, liftout design, high impact, durable ABS. Removable, anti-splash grid diverts dripwater into receptacle.

COLD WATER THERMOSTAT

Temperature is controlled to 4°C - 10°C by adjustable thermostat, easily accessible on back.

HOT WATER

Hygienic type stainless steel. Highly efficient internal heating element. Fire proof insulation.

FAUCETS

Durable polypropylene. Self-closing type. Easy to operate.

COLOR

Off white, Dark Grey, Wine Red.

HOT WATER TANK

Hygienic type stainless steel. Highly efficient internal heating element. Fire proof insulation.

WARRANTY

One year on the sealed refrigeration system and most component parts.

COLD WATER TANK

Hygienic stainless steel.

