

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project : | | |
|-----------------|------|--|
| Model #: | | |
| Item #: | Qty: | |
| Available W/H : | | |
| Approval : | | |

Mega Top Unit - Slide Back Lid

Food Prep Tables Super Deluxe Series

Model: TST-48SD-18-N-SL

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.





Removable cover with slide back lid

___ FEATURES & BENEFITS =__

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing

- Digital temperature control & monitor system Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.
- Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

LED interior lighting & fan control

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior (ABS door liner) and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

Removable insulated slide-back lid

Removable hood and slide-back lid are easy to clean while providing a better view of the top opening.

- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail
- High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place high density, CFC free polyurethane insulation.

■ Refrigerator holds 33°F ~ 39°F for the best in food preservation











| RAL gerant | Intertek | Intertek | U.S.A | 3 YEAR | S YEAR WARRANTY (U.S.A.only) |
|------------|----------|----------|-------|--------|------------------------------------|
| | | | | | |

| Model | Swing Door | CU./FT. | #of Shelves | #of Pans | НР | AMPS | Crated Weight (lbs.) | L x D [*] x H [†] (inches) |
|------------------|---------------|---------|----------------|-------------|-----|------|-------------------------|--|
| TST-48SD-18-N-SL | 2 | 15 | 2 | 18 | 1/5 | 4.1 | 265 | 481/4 x 37 x 39 |

(unit: inch)

Mega Top Unit - Slide Back Lid

Model: TST-48SD-18-N-SL

| ELECTRICAL DATA | | | | |
|----------------------------|----------------|--|--|--|
| Voltage | 115/60/1 | | | |
| Plug Type | ① NEMA 5-15P | | | |
| Full Load Amperes | 4.1 | | | |
| Compressor HP | 1/5 | | | |
| Cord Length (ft.) | 9 | | | |
| Refrigerant R-290 | | | | |
| DIMENSIONAL DATA | | | | |
| Ext. Length Overall (in.) | 481/4 (1226mm) | | | |
| Ext. Depth Overall (in.)* | 37 (939mm) | | | |
| Ext. Height Overall (in.)† | 39 (992mm) | | | |
| # of Doors | 2 | | | |
| # of Shelves | 2 | | | |
| # of Pans | 18 | | | |
| # of Hood | 1 | | | |
| Net Capacity (cu. ft.) | 15 | | | |
| Net Weight (lbs.) | 245 | | | |
| Gross Weight (lbs.) | 265 | | | |
| Shelf Size (in.) | 21 x 17 | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Anti-corrosion coated evaporator
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- 2.5" dia. casters available (optional) & Legs available (optional)
- Stainless steel double overshelf available (optional)


■ OPTIONAL ACCESSORIES :

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional stainless steel shelf: M727800100
- ☐ Stainless steel double overshelf: TSOS-4R
- Door lock: extra lead time will apply, please call factory for more details to order

PLAN VIEW



PLAN VIEW



SIDE VIEW

Ver 20171107


















■ Warranty: 800-381-7770 ■ AC: 888-900-1002









^{*} Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.

^{**} Please allow 4 weeks lead time for shipping. Please call factory for more details to place an order.