

4184 E. Conant St. Long Beach, CA 90808 Tel. 888-900-1002 Fax. 310-900-1088 www.turboairinc.net

Project :	
Model #:	
Item #:	Qty:
Approval:	

## Top Mount Package Units (SMART 7)

Model : STX130MR448A2



## \_\_\_FEATURES / BENEFITS =\_\_

#### SM 1: Blue Anti-corrosion-fin and Coated Copper Tube

Protects aluminum and copper pipes from toxic gases generated from foods, retards refrigerant leakage, and prolongs the cooling capacity.

#### SM 2: Expansion Valve

**SMART** 

Allows safe storage of foods with a feature that self-adjusts the circulation of refrigerant as the internal temperature changes, thus recovering the required temperature quickly.

#### **SM 3: Compressor Protected Solenoid Valve**

Decreases the inflow of refrigerant into the compressor when it is restarted after a stop. This extends compressor life and reduces compressor failure.

#### SM 4: 18% Bigger Condenser than the Standard

The condenser's efficiency affects most of the refrigerator's performance. Particularly, when used in a small compartment under high ambient temperatures or a dusty area, the package unit's condenser needs to be bigger than standard ones in order to achieve the best performance. In consideration of the environments that our products may be subject to, condensers utilized in our products are 18% larger than competitors'.

#### SM 5: Energy Efficient EC Motor

Through the use of highly efficient EC motors, our products reduce energy consumption and lower electricity costs, thus protecting the environment. Our products are designed with easy-to-replace motor and fan blades.

#### SM 6: Leak Free Patented Hot Gas Condensate System

The hot gas condensate system is an ideal system because of its fast evaporation of condensed water and its enhancing refrigeration efficiency. In spite of these advantages, many companies have stopped the application of such a system because of the high risk of discarding the refrigerators due to the rapid corrosion of hot gas lines causing refrigerant leakage and water inflow into the cooling pipes. Such problems are completely resolved in our products, thanks to a patented technology that prevents pipes from corrosion.

#### SM 7: Highly Efficient Air Circulation Enclosure

This system is designed to release hot air to the outside faster than competitors' and to enhance cooling efficiency. At the same time, it retards elevation of compressor temperature and keeps refrigerant pressure from increasing, thus saving energy as a result.











# Top Mount Package Units (SMART 7)

## Model: STX130MR448A2

## Performance Data - Medium Temperature Model, Air Defrost

Model		Capacity BTU / HR (Ambient Temp)														
		80°F			90°F			95°F		100°F			110°F			
		Room Temperature °F														
		34°F	35°F	38°F	34°F	35°F	38°F	34°F	35°F	38°F	34°F	35°F	38°F	34°F	35°F	38°F
	STX130MR448A2	13982	14292	15091	13302	13679	14443	12876	13242	13981	12449	12717	13426	11481	11812	12435

### **Unit Specifications - Medium Temperature Model**


Model	Power Supply						Evaporator	Plug	Matching NEMA	Sound	Net Weight	AWEF
	Voltage	PH	Hz	MCA	MOPD	Amps	CFM	Supplied	Receptacle	dBA	lbs (kg)	Value
STX130MR448A2	208-230	1	60	16.1	25	13.4	1625	† NO	-	73	317 (144)	7.6

Design and specifications subject to change without notice.

■ WARRANTY: 2 Year Compressor and Parts Warranty & 1 Year Labor Warranty

**PLAN VIEW** (unit: inch)

Opening Size: 25" x 38.5"



477/16 381/16 115/16 **1**15/16 4115/16 **SIDE VIEW** 

Ver.20210519









■ **Toll Free**: 888-900-1002









