Feljowes. (Array" Wall AW1 & Stand AS1

Technical Specifications		
Max Air Flow (CFM) 240		
Fan Speeds (CFM) 68, 90, 110, 140, 240		
Sound Pressure Levels (dB per ISO 3746)	AS1: 29, 34, 38, 44, 57 AW1: 28, 33, 38, 44, 56	
Power Requirements	AC120V/60Hz/0.9A	
Power Consumption (watts)	6, 9, 13, 24, 96	
IoT Connectivity	LTE	
Modes Auto, Quiet, Manual		
Filter Change Indicator Yes		
Air Intake	Bottom, Sides	
Air Outlet	Тор	
Warranty	5-Year Limited	



Λ	C	1
\vdash	J	J

Code	Dimensions (LxWxH)	Weight (lbs.)	Color
5884801 (Wall)	20.9 x 9.7 x 19.6	20	White
5884201 (Stand)	20.9 x 10.2 x 22.8	25	

RESET Air Class B IAQ Sensors	Accuracy
PM2.5 PM10	≤ 100µg/m³: ± 15µg/m³ > 100µg/m³: ± 15%
CO2	± (30ppm+3%)
VOC/TVOC	± 30ppm
Temperature	0.2C
RH	1.80%

Area Coverage (SQFT)			
eACH	Ceiling Height (ft)		(ft)
	8	10	12
1	1,800	1,440	1,200
3	600	480	400
5	360	288	240

Virus Testing	
H1N1	
Rhinovirus	
SARS-CoV-2*	


Monitoring and Comfort Sensors
Pressure
Light
Occupancy
Sound

Certifications		
	CARB*	
	FCC	
	UL 507	
	EN1822M	



$\Box \Box \Box$	LOVYOR	Cada	013600	1

AW1 & AS1 Filter		
Filter Type	Hybrid Filter (Carbon, H13 True HEPA)	
Filter Rating	H13 True HEPA	
Filter Efficiency	99.95% @ 0.1 microns	
Antimicrobial Coating	Yes	
Estimated Filter Life	12 months	
Pack Size	2PK - Includes Pre-Filter	



	Wall AW1	Stand AS1
Mounting Type	Wall mounted Drywall anchors included	• Floor stand
Electrical Requirements	AC120V/60Hz/0.9AConstant Power SupplyHardwired	 AC120V/60Hz/0.9A Grounded 3 prong AC plug included, 62" length
Hardware Provided	Drywall anchors - 10mm OD Pan Head Phyllips Screws	• None, stand comes pre-installed
Anchor Materials By Others	• Wire nuts	• None
Clearance	Recommended minimum 8" of clearance above the unit	• None