

# Fellowes Array™ Wall AW2 & Stand AS2

## Technical Specifications

Max Air Flow (CFM)	400
Fan Speeds (CFM)	120, 150, 200, 260, 400
Sound Pressure Levels (dB per ISO 3746)	AS2: 28, 34, 39, 45, 58 AW2: 27, 33, 37, 44, 58
Power Requirements	AC120V/60Hz/1.5A
Power Consumption (watts)	10, 14, 23, 41, 152
IoT Connectivity	LTE
Modes	Auto, Quiet, Manual
Filter Change Indicator	Yes
Air Intake	Bottom, Sides
Air Outlet	Top
Warranty	5-Year Limited



AW2

AS2

Code	Dimensions (L x W x H)	Weight (lbs.)	Color
5885101 (Wall)	34.7 x 9.4 x 19.7	35	White
5884501 (Stand)	34.7 x 10.6 x 22.8	40	

## RESET Air Class B IAQ Sensors

## Accuracy

PM2.5 PM10	$\leq 100\mu\text{g}/\text{m}^3$ : $\pm 15\mu\text{g}/\text{m}^3$ $> 100\mu\text{g}/\text{m}^3$ : $\pm 15\%$
CO2	$\pm (30\text{ppm}+3\%)$
VOC/TVOC	$\pm 30\text{ppm}$
Temperature	0.2C
RH	1.80%

## Area Coverage (SQFT)

eACH	Ceiling Height (ft)		
	8	10	12
1	3,000	2,440	2,000
3	1,000	800	666
5	600	480	400

## Virus Testing

H1N1
Rhinovirus
SARS-CoV-2*

## Monitoring and Comfort Sensors

Pressure
Light
Occupancy
Sound

## Certifications

CARB*
FCC
UL 507
EN1822M




Fellowes Code: 9436902




## AW2 & AS2 Filter

Filter Type	Hybrid Filter (Carbon, H13 True HEPA)
Filter Rating	H13 True HEPA
Filter Efficiency	99.95% @ 0.1 microns
Antimicrobial Coating	Yes
Estimated Filter Life	12 months
Pack Size	2PK- Includes Pre-Filter

\* Subject to final compliance certificate



Power Connection



	Wall AW2	Stand AS2
<b>Mounting Type</b>	<ul style="list-style-type: none"> <li>• Wall mounted</li> <li>• Drywall anchors included</li> </ul>	<ul style="list-style-type: none"> <li>• Floor stand</li> </ul>
<b>Electrical Requirements</b>	<ul style="list-style-type: none"> <li>• AC120V/60Hz/1.5A</li> <li>• Constant Power Supply</li> <li>• Hardwired</li> </ul>	<ul style="list-style-type: none"> <li>• AC120V/60Hz/1.5A</li> <li>• Grounded 3 prong AC plug included, 62" length</li> </ul>
<b>Hardware Provided</b>	<ul style="list-style-type: none"> <li>• Drywall anchors - 10mm OD</li> <li>• Pan Head Phillips Screws</li> </ul>	<ul style="list-style-type: none"> <li>• None, stand comes pre-installed</li> </ul>
<b>Anchor Materials By Others</b>	<ul style="list-style-type: none"> <li>• Wire nuts</li> </ul>	<ul style="list-style-type: none"> <li>• None</li> </ul>
<b>Clearance</b>	<ul style="list-style-type: none"> <li>• Recommended minimum 8" of clearance above the unit</li> </ul>	<ul style="list-style-type: none"> <li>• None</li> </ul>