

ltem#:	178AU72R		Project:	
Otv:		Date:		Approval:

Avantco AU-72R 72" Undercounter Refrigerator

Item #178AU72R







Technical Data

Width	71 1/2 Inches	
Depth	29 1/2 Inches	
Height	35 1/4 Inches	
Power Cord Length	7 Feet	
Interior Width	67 9/16 Inches	
Shelf Width	21 7/16 Inches	
Interior Depth	25 Inches	
Shelf Depth	22 3/16 Inches	
Interior Height	26 1/8 Inches	
Work Surface Height	35 1/4 Inches	

Features

- 430 type stainless steel exterior and aluminum interior with 304 type stainless steel floor
- Compact, undercounter size takes up minimal space
- Easy-to-read digital temperature controller and auto-defrost function
- Self-closing and stay-open door features for easy loading and unloading
- Uses R-290 refrigerant; 115V, 1/5 hp

Certifications



ETL, US



5-15P




ETL Sanitation



Technical Data

Amps	2.7 Amps	
Hertz	60 Hz	
Phase	1 Phase	
Voltage	115 Volts	
Wattage	310.5 Watts	
Access Type	Doors	
BTU (LBP)	860 BTU	
Capacity	21.13 cu. ft.	
Capacity (per Shelf)	66.13999938964844 lb.	
Casters	With Casters	
Compressor Location	Rear Mounted	
Compressor Style	Side / Rear Breathing	
Construction	Stainless Steel and Aluminum	
Door Style	Swing	
Door Type	Solid	
Features	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets Self-Closing Doors Stay-Open Doors	
Hinge Location	Left Right	
Horsepower	1/5 hp	
Number of Doors	3 Doors	
Number of Shelves	3 Shelves	
Plug Type	NEMA 5-15P	
Refrigerant Type	R-290	
Style	Counter Height	
Temperature Range	33 - 40 Degrees F	
Туре	Refrigerators Undercounter Refrigerators	

Plan View





Notes & Details

Invest in this Avantco 72" undercounter refrigerator for a dependable cold food storage solution. With a spacious refrigerator portion readily accessible through its 3 doors, the unit opens up to 3 shelves that will aid in organizing your ingredients. Plus, because they each accommodate up to 66.14 lb., the included PVC-coated wire shelves are well-equipped for holding heavy bulk ingredients, from dozens of eggs to jars of condiments and sauces.

This unit is designed for outstanding durability to ensure that it withstands busy kitchen environments with ease. It features a stainless steel exterior, which provides both strength and a smooth, sleek appearance. The painted aluminum interior with a 304 type stainless steel floor also offers the stability necessary for heavy, regular use. Because of its undercounter design, the refrigerator effortlessly adds cold storage space beneath a pre-existing countertop and doesn't require additional space for its own footprint. This makes the unit ideal for busy operations in need of storage, but tight on back-of-house space. Plus, it comes with 4 reliable casters, 2 of which are braking casters, for easy mobility around your establishment.

This unit ensures optimal performance by operating with a 1/5 hp refrigeration system that circulates R-290 refrigerant to maintain temperatures from 30 to 40 degrees Fahrenheit. R-290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps provide structural rigidity and maintain internal temperatures.

Operation of the refrigerator is easy, thanks to its special features. Monitor temperatures by consulting the interior wall-mounted thermometer and use the auto-defrost feature on the pre-programmed digital controller to keep the unit in excellent shape. Take advantage of the included casters and roll the unit aside to thoroughly clean the area as needed. This undercounter refrigerator requires a 115V electrical connection for operation and comes with a 7' power cord.

MARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.