

Item#:	178GDC24FBC		Project:	
\bigcap tv		Data		Approvale

Avantco GDC-24F-HC 31 1/8" Black Swing Glass Door Merchandiser Freezer with LED Lighting and Customizable Panel

Item#178GDC24FBC







Technical Data

31 1/8 Inches	
33 1/4 Inches	
86 13/16 Inches	
96 Inches	
25 1/4 Inches	
28 3/8 Inches	
62 Inches	
4.9 Amps	
1 Phase	
115 Volts	

Features

- 1 self-closing, anti-fog swing glass door
- Temperature range: -8 to -1 degrees Fahrenheit
- R290 refrigerant
- Interior LED lighting
- 115V, 1 hp; 4.9 Amps

Certifications










Technical Data

Access Type	Doors	
BTU (LBP)	2730 BTU	
Capacity	23 cu. ft.	
Capacity (per Shelf)	90 lb.	
Color	Black	
Compressor Location	Bottom Mounted	
Door Style	Swing	
Door Type	Glass	
Features	Customizable LED Lighting Lighted Interior Self-Closing Doors	
Horsepower	1 hp	
Interior Color	White	
Number of Doors	1 Doors	
Number of Shelves	4 Shelves	
Plug Type	NEMA 5-15P	
Refrigerant Type	R-290	
Sections	1 Section	
Temperature Range	-81 Degrees F	

Plan View



Notes & Details

Increase impulse sales of frozen meals, novelty treats, fruits, and vegetables with this Avantco GDC-24F-HC 31 1/8" black merchandising freezer! Designed with sharp looks and usability in mind, this unit is the perfect display for your products with its sleek finish. And, since the housing is made from black coated steel, you can be sure that it will provide superior durability. This unit boasts an anti-fogging glass swing door to ensure that customers always have a clear view of your products, while 4 epoxy coated steel shelves help you stay organized. Plus, the shelves easily adjust to accommodate prepackaged foods in a variety of sizes. Interior LED lighting also works to illuminate and further merchandise your products.

Designed to maintain temperatures from -8 to -1 degree Fahrenheit, this freezer boasts a bottom-mounted 1 hp compressor that runs on R290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include a self-closing mechanism on the door, automatic defrosting, as well as a digital temperature control and display. This item requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.