© 2025 Avantco Refrigeration

Item #:	178GDC49FWC	Project:

Qty: _____ Date: _____ Approval: _____

Avantco GDC-49F-HC 53 1/8" White Swing Glass Door Merchandiser Freezer with LED Lighting and Customizable Panel

Item #178GDC49FWC

REFRIGERATION





Technical Data

53 1/8 Inches
31 7/8 Inches
83 7/8 Inches
96 Inches
50 Inches
28 3/8 Inches
61 7/8 Inches
6.97 Amps
1 Phase
115 Volts

Features

- 2 self-closing, anti-fog swing glass doors •
- Temperature range: -8 to -1 degrees Fahrenheit
- Easy-to-use digital temperature controls
- Interior LED lighting •
- 115V, 1 1/2 hp; 6.97 Amps; R290 refrigerant

Certifications








Tec	hnica	l Data
100	mee	Dutu

BTU (LBP)	3732 BTU
Capacity	37.08 cu. ft.
Capacity (per Shelf)	90 lb.
Color	White
Compressor Location	Bottom Mounted
Door Style	Swing
Door Type	Glass
Features	Customizable LED Lighting
Hinge Location	Left Right
Horsepower	1 1/2 hp
Installation Type	Freestanding
Interior Color	White
Number of Doors	2 Doors
Number of Shelves	8 Shelves
Refrigerant Type	R-290
Sections	2 Sections
Temperature Range	-81 Degrees F

Plan View



Notes & Details

Increase impulse sales of frozen meals, novelty treats, fruits, and vegetables with this Avantco GDC-49F-HC 53 1/8" white merchandising freezer! Designed with sharp looks and usability in mind, this unit is the perfect display for your products with its sleek finish. And, since the housing is made from white-coated steel, you can be sure that it will provide superior durability. This unit boasts 2 anti-fogging glass swing doors to ensure that customers always have a clear view of your products, while 8 epoxy-coated steel shelves help you stay organized. Plus, the shelves easily adjust to accommodate prepackaged foods in a variety of sizes. Interior LED lighting also works to illuminate and further merchandise your products.

Designed to maintain temperatures from -8 to -1 degree Fahrenheit, this freezer boasts a bottom-mounted 1 1/2 hp compressor that runs on R290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed in place using polyurethane insulation. Other helpful features include a self-closing mechanism on the doors, automatic defrosting, as well as a digital temperature control and display. This item requires a 115V electrical connection for operation.

A WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.