

ltem #: <u>1780</u>	GDC49WC	Project:	
Ot	Data	Δ	un vale

Avantco GDC-49-HC 53" White Swing Glass Door Merchandiser Refrigerator with LED Lighting and Customizable Panel

Item#178GDC49WC







Technical Data

Width	53 1/8 Inches	
Depth	31 7/8 Inches	
Height	83 7/8 Inches	
Power Cord Length	96 Inches	
Interior Width	50 Inches	
Interior Depth	28 3/8 Inches	
Interior Height	61 7/8 Inches	
Amps	3.14 Amps	
Phase	1 Phase	
Voltage	115 Volts	

Features

- 2 self-closing, anti-fog swing glass doors; great for displaying prepackaged food
- Temperature range of 33 to 40 degrees Fahrenheit
- R290 refrigerant
- Interior LED lighting; 4" casters included
- 115V, 1/4 hp; 3.14 Amps

Certifications








ETL, US 5-15P Customizable



Technical Data

Access Type	Doors	
BTU (LBP)	1285 BTU	
Capacity	42.5 cu. ft.	
Capacity (per Shelf)	90 lb.	
Color	White	
Compressor Location	Bottom Mounted	
Door Style	Swing	
Door Type	Glass	
Features	Customizable LED Lighting	
Hinge Location	Left Right	
Horsepower	1/4 hp	
Installation Type	Freestanding	
Interior Color	White	
Number of Doors	2 Doors	
Number of Shelves	8 Shelves	
Plug Type	NEMA 5-15P	
Refrigerant Type	R-290	
Sections	2 Sections	
Temperature Range	33 - 40 Degrees F	
Туре	Merchandising Refrigeration	

Plan View



Notes & Details

Increase your sales of "grab and go" items like bottled tea and soda, or pre-packaged sandwiches and salads with this Avantco GDC-49-HC 53" white merchandising refrigerator! Designed with sharp looks and usability in mind, this unit is the perfect display for your products with its sleek white finish and a lighted top graphics area. And, since the housing is made from white coated steel, you can be sure that it will provide superior durability. Additionally, it boasts 2 anti-fogging glass swing doors to ensure that customers always have a clear view of your products, while 8 epoxy coated steel shelves help you stay organized. Each shelf can hold up to 90 lb. of product. Plus, the shelves easily adjust to accommodate changing inventory and menus. Interior LED lighting on the right side also works to illuminate and further merchandise your products.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a bottom-mounted 1/4 hp compressor that runs on R290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include a self-closing mechanism on the doors, automatic defrosting, and a digital temperature control. This item requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.