



Item #: 178GDC69HCB Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco GDC-69-HC 78 1/4" Black Customizable Swing Glass Door Merchandiser Refrigerator with LED Lighting

Item #178GDC69HCB



Technical Data

Width	78 1/4 Inches
Depth	30 Inches
Height	80 5/16 Inches
Power Cord Length	96 1/2 Inches
Interior Width	73 1/2 Inches
Left Door Opening Width	21 5/8 Inches
Left/Right Shelf Width	23 1/4 Inches
Middle Door Opening Width	22 1/16 Inches
Middle Shelf Width	25 13/16 Inches
Right Door Opening Width	21 5/8 Inches

Features

- Anti-fog dual-pane tempered glass swing doors with magnetic gaskets
- Interior LED lighting illuminates product; back lit exterior top panel attracts customers' attention
- 8 adjustable shelves with price tag strip on each shelf
- Easy to use digital temperature controls
- 115V; 4/5 hp compressor; R-290 refrigerant

Certifications



Avantco Refrigeration

Plan View



Notes & Details

Increase your sales of "grab and go" items like bottled tea and soda, or pre-packaged sandwiches and salads with this Avantco GDC-69-HC 78 1/4" black merchandising refrigerator! Designed with sharp looks and usability in mind, this unit is the perfect display for your products with its sleek finish. And, since the housing is made from black coated steel, you can be sure that it will provide superior durability. This unit boasts 3 anti-fogging, dual-pane tempered glass swing doors to ensure that customers always have a clear view of your products, while 8 epoxy-coated steel shelves help you stay organized. Plus, the shelves easily adjust to accommodate salads, wraps, or sandwiches. Interior LED lighting on the right side also works to illuminate and further merchandise your products.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a bottom-mounted 4/5 hp compressor that runs on R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the bottom-mounted design makes it easy for employees to load and unload products due to the raised bottom shelf. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include magnetic gaskets, automatic defrosting, and a digital temperature control. This item requires a 115V electrical connection for operation. This multi-door unit has one left hinge and two right hinges.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.