

| ltem#: | 1/8SSCF160HC |       | Project: |           |
|--------|--------------|-------|----------|-----------|
|        | •            |       |          |           |
| Otv.   |              | Date: |          | Approval: |

# Avantco SS-CFT-60-HC 60" Stainless Steel Refrigerated Salad Bar / Cold **Food Table**

Item#178SSCFT60HC







# **Technical Data**

| Width                       | 60 3/8 Inches  |  |
|-----------------------------|----------------|--|
| Depth                       | 29 1/2 Inches  |  |
| Height                      | 34 5/8 Inches  |  |
| Power Cord Length           | 98 Inches      |  |
| Interior Width              | 56 1/2 Inches  |  |
| Left Door Opening Width     | 26 1/16 Inches |  |
| Right Door Opening<br>Width | 26 1/16 Inches |  |
| Shelf Width                 | 27 1/4 Inches  |  |
| Interior Depth              | 19 7/8 Inches  |  |
| Shelf Depth                 | 17 Inches      |  |

#### **Features**

- Perfect for buffets, cafeterias, and other self-service applications
- Durable stainless steel construction
- Accepts 4" and 6" deep standard 1/3 and 1/6 food pans
- Digital control with auto defrost
- Uses R290 refrigerant; 115V; 1/4 hp

### Certifications





**ETL Sanitation** 




ETL, US & Canada



#### **Technical Data**

| Height Style                | Standard Height                 |  |
|-----------------------------|---------------------------------|--|
| Interior Height             | 25 3/4 Inches                   |  |
| Amps                        | 5.4 Amps                        |  |
| Phase                       | 1 Phase                         |  |
| Voltage                     | 115 Volts                       |  |
| Wattage                     | 540 Watts                       |  |
| Capacity                    | 19.5 cu. ft.                    |  |
| Capacity (per Shelf)        | 88 lb.                          |  |
| Casters                     | With Casters                    |  |
| Color                       | Silver                          |  |
| Full Size Food Pan Capacity | 4 Pans                          |  |
| Horsepower                  | 1/4 hp                          |  |
| Material                    | Stainless Steel                 |  |
| Number of Shelves           | 2 Shelves                       |  |
| Plug Type                   | NEMA 5-15P                      |  |
| Refrigerant Capacity        | 3.5 oz.                         |  |
| Refrigerant Type            | R-290                           |  |
| Shape                       | Rectangle                       |  |
| Starting Amps               | 16.2 Amps                       |  |
| Starting Wattage            | 1620 Watts                      |  |
| Style                       | Refrigerated<br>Standard Height |  |
| Temperature Range           | 33 - 40 Degrees F               |  |
| Туре                        | Food Tables<br>Salad Bars       |  |

## **Plan View**



### **Notes & Details**

Create a convenient cold food serving area with this Avantco SS-CFT-60-HC 60" stainless steel refrigerated salad bar / cold food table! It's a sleek addition to any buffet, cafeteria, or other front-of-house area.

The construction of this unit is designed with commercial use in mind. It features a 430 type stainless steel exterior and 304 type stainless steel interior, which are fortified with foamed-in-place polyurethane insulation. The insulation also helps to promote proper temperature retention. The unit can accommodate up to (12) 1/3 size or (24) 1/6 size 8" deep food pans (sold separately). These are great for holding common sandwich or salad toppings, from eggs and cheese to green pepper or ham. (2) 273/8" x 171/8" plastic-coated steel shelves are included and each accommodate up to 88 lb. of weight, helping to organize your assorted supplies in the refrigerated cabinet. The cabinet is easily accessed by a full-length stainless steel handle on each door.

High-quality performance is made possible by the unit's 1/4 hp refrigeration system, which maintains temperatures between 33 and 40 degrees Fahrenheit. It does this by circulating R290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3.

For operation, this table requires a 115V electrical connection.



▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <a href="https://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>.