

ltem#:	1/8SSUC2/RA		Project:	
Otv:		Date:		Approval:

Avantco SS-UC-27R-HC 27" Stainless Steel ADA Height Undercounter Refrigerator

Item#178SSUC27RA







Technical Data

Width	27 Inches	
Depth	29 1/2 Inches	
Height	33 5/8 Inches	
Power Cord Length	84 Inches	
Interior Width	22 1/4 Inches	
Interior Depth	22 7/8 Inches	
Interior Height	23 1/2 Inches	
Work Surface Height	33 5/8 Inches	
Amps	2.2 Amps	
Hertz	60 Hz	

Features

- 2 1/2" casters make moving simple for easy cleaning and bring the unit to an ADAcompliant working h
- Strong and sleek type 430 stainless steel exterior and type 304 stainless steel interior for maximum
- Foamed-in-place polyurethane maintains temperatures from 33 to 40 degrees
- Easy-to-read digital temperature controller and auto-defrost function
- 115V; 1/4 hp

Certifications










ETL Sanitation



Technical Data

Phase	1 Phase	
Voltage	115 Volts	
Wattage	210 Watts	
Access Type	Doors	
Backsplash	Without Backsplash	
BTU (LBP)	666 BTU	
Capacity	5.5 cu. ft.	
Capacity (per Shelf)	88 lb.	
Color	Silver	
Door Style	Swing	
Door Type	Solid	
Features	ADA Compliant Removable Magnetic Door Gaskets	
Horsepower	1/4 hp	
Number of Doors	1 Doors	
Number of Shelves	1 Shelf	
Plug Type	NEMA 5-15P	
Refrigerant Type	R-290	
Starting Amps	6.6 Amps	
Starting Wattage	630 Watts	
Style	ADA Height	
Temperature Range	33 - 40 Degrees F	
Top Capacity	318 lb.	
Туре	Refrigerators Undercounter Refrigerators	

Plan View





Notes & Details

Make cold food storage as convenient as possible with the Avantco 27" undercounter refrigerator. With a spacious refrigerated portion readily accessible through its door, the unit opens up to a shelf to help you organize your ingredients and best utilize the 5.5 cu. ft. interior. Plus, because it accommodates up to 88 lb., the epoxy-coated steel shelf is well equipped for holding heavy bulk ingredients, from dozens of eggs to jars of condiments and sauces.

This unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments with ease. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use. Because of its undercounter design, the unit effortlessly adds refrigerated storage space without requiring space devoted solely to its footprint. This unit features a field reversible door (reversible hinge hardware sold separately) to make adjusting this unit to your workflow easier.

This refrigerator ensures optimal performance by operating with a 1/4 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to add rigidity to the body's structure.

Operation of the refrigerator is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. At the end of the day, take advantage of the casters and roll the unit aside to thoroughly clean the area. This undercounter unit requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.