

ltem#:	178SSWD3RI		Project:	
0 1		D .		
Otv·		L)ate:		Annroval:

Avantco 93" Stainless Steel Extra Deep Worktop Refrigerator with 3 1/2" Backsplash with 2 Left Drawers and 2 Doors

Item#178SSWD3RI







Technical Data

Width	93 13/16 Inches
Depth	31 1/2 Inches
Height	38 Inches
Power Cord Length	98 Inches
Interior Width	73 1/4 Inches
Packaging Width	96 9/16 Inches
Shelf Width	23.149999618530273 Inches
Depth with Door Open	55 1/16 Inches
Interior Depth	26 3/16 Inches
Packaging Depth	34 1/4 Inches

Features

- Strong and sleek type 430 stainless steel exterior with type 304 stainless steel
- Foamed-in-place polyure than e insulation maintains temperatures from $33\,\mathrm{to}\,40$ degrees Fahrenheit
- 3 1/2" backsplash for wall protection
- Includes 2 left-side drawers, 2 doors, and 6 divider bars
- 115V; 1/4 hp
- Note: only the worktop refrigerator holds the ETL certification

Certifications





ETL Sanitation



ETL, US




Technical Data

Interior Height	Shelf Depth	24 2/5 Inches	
Work Surface Height 35 1/4 Inches Amps 5.7 Amps Hertz 60 Hz Phase 1 Phase Voltage 115 Volts Wattage 524 Watts Access Type Doors and Drawers BTU (LBP) 809 BTU Capacity (per Shelf) 90 lb. Capacity (per Shelf) 90 lb. Compressor Style Front / Rear Breathing Door Style Swing Door Type Solid Features Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash Hinge Location Left Removable Magnetic Drawer Gaskets Horsepower 1/4 hp Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Doors 2 Doors Number of Drawers 2 Drawers Number of Drawers 2 Drawers Number of Shelves 1 Shelf Plug Type<	Interior Height	22 7/8 Inches	
Amps 5.7 Amps Hertz 60 Hz Phase 1 Phase Voltage 115 Volts Wattage 524 Watts Access Type Doors and Drawers BTU (LBP) 809 BTU Capacity 254 cu. ft. Capacity 90	Packaging Height	39 Inches	
Hertz	Work Surface Height	35 1/4 Inches	
Phase 1 Phase Voltage 115 Volts Wattage 524 Watts Access Type Doors and Drawers BTU (LBP) 809 BTU Capacity 254 cu. ft. Capacity (per Shelf) 90 lb. Compressor Style Front / Rear Breathing Door Style Swing Door Type Solid Features Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gakets Removable Magnetic Door Gakets Removable Magnetic Doraver Gaskets Vill Backsplash Hinge Location Left Right Horsepower 1/4 hp Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Doors 2 Doors Number of Shelves 1 Shelf Plug Type NEMA 5-15P Refrigerant Type Ref Refrigerant Type Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Te	Amps	5.7 Amps	
Voltage 115 Volts Wattage 524 Watts Access Type Doors and Drawers BTU (LBP) 809 BTU Capacity 25.4 cu. ft. Capacity (per Shelf) 90 lb. Compressor Style Front / Rear Breathing Door Style Swing Door Type Solid Features Voltage Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets Remov	Hertz	60 Hz	
Wattage 524 Watts Access Type Doors and Drawers BTU (LBP) 809 BTU Capacity 25.4 cu. ft. Capacity (per Shelf) 901b. Compressor Style Front / Rear Breathing Door Style Swing Door Type Solid Features Solid Hinge Location Left Right Horsepower 1/4 hp Insulation Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Drawers 2 Drawers Number of Shelves 15 Held Shelpe Steel Refrigerant Type Regards Steel Stairless Agenda Steel Stairless Agenda Steel Steel Stairless Agenda Steel Steel Stairless Steel St	Phase	1 Phase	
Access Type BTU (LBP) 809 BTU Capacity 25.4 cu. ft. Capacity (per Shelf) 90 lb. Compressor Style Front / Rear Breathing Door Style Swing Door Type Solid Features Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Dorawer Gaskets With Backsplash Hinge Location Left Right Horsepower 1/4 hp Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Drawers Number of Brawers Number of Shelves 1 Shelf Plug Type NEMA 5-15P Refrigerant Type Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 33-40 Degrees F	Voltage	115 Volts	
BTU (LBP) Capacity Capacity Capacity (per Shelf) Pour Style Door Style Door Type Solid Features Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Drawer Gaskets With Backsplash Hinge Location Left Right Horsepower 1/4 hp Insulation Material Material Material Matwinum Ambient Temperature 90 Degrees F Net Weight Number of Doors Number of Drawers Number of Shelves 1 Shelf Plug Type Refrigerant Type Refrigerant Type Starting Amps 17.1 Amps Starting Wattage Style Counter Height Temperature Range 32-40 Degrees F	Wattage	524 Watts	
Capacity 25.4 cu. ft. Capacity (per Shelf) 90 lb. Compressor Style Front / Rear Breathing Door Style Swing Door Type Solid Features Solid Hinge Location Left Right Ri	Access Type	Doors and Drawers	
Capacity (per Shelf) 90 lb. Compressor Style Front / Rear Breathing Door Style Swing Door Type Solid Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets Removable Magnetic Door Gaskets With Backsplash Hinge Location Left Right Horsepower 1/4 hp Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Doors 2 Doors Number of Drawers 2 Drawers Number of Shelves 1 Shelf Plug Type NEMA 5-15P Refrigerant Type R-290 Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 33 - 40 Degrees F	BTU (LBP)	809 BTU	
Compressor Style Door Style Swing Door Type Solid Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets Removable Magneti	Capacity	25.4 cu. ft.	
Door Style Swing Door Type Solid Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets Removable Magnetic Door Gaskets Removable Magnetic Door Gaskets With Backsplash Hinge Location Left Right Horsepower 1/4 hp Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Doors 2 Doors Number of Drawers 2 Drawers Number of Shelves 1 Shelf Plug Type NEMA 5-15P Refrigerant Type R-290 Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 33-40 Degrees F	Capacity (per Shelf)	90 lb.	
Door Type Solid Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets Removable Magnetic Drawer Gaskets With Backsplash Hinge Location Left Right Horsepower 1/4 hp Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Doors 2 Doors Number of Drawers 1 Shelf Plug Type NEMA 5-15P Refrigerant Type Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 33-40 Degrees F	Compressor Style	Front / Rear Breathing	
Features Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets With Backsplash Hinge Location Left Right Horsepower 1/4 hp Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Doors 2 Doors Number of Drawers 1 Shelf Plug Type NEMA 5-15P Refrigerant Type Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Controller Removable Magnetic Door Saskets With Backsplash Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Saskets With Backsplash Polyurethane Foam 90 Degrees F Net Weight 342 lb. Number of Doors 1 Shelf Plug Type NEMA 5-15P Refrigerant Type Starting Amps 17.1 Amps Starting Wattage 33-40 Degrees F	Door Style	Swing	
Features Digital Temperature Controller Removable Magnetic Door Gaskets Removable Magnetic Drawer Gaskets With Backsplash Hinge Location Left Right Horsepower 1/4 hp Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Doors 2 Doors Number of Drawers 2 Drawers Number of Shelves 1 Shelf Plug Type NEMA 5-15P Refrigerant Type R-290 Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 33 - 40 Degrees F	Door Type	Solid	
Horsepower 1/4 hp Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Doors 2 Doors Number of Drawers 2 Drawers Number of Shelves 1 Shelf Plug Type NEMA 5-15P Refrigerant Type R-290 Starting Amps 17.1 Amps Starting Wattage 1572 Watts Temperature Range 33-40 Degrees F	Features	Digital Temperature Controller Removable Magnetic Door Gaskets Removable Magnetic Drawer Gaskets	
Insulation Material Polyurethane Foam Material Stainless Steel Maximum Ambient Temperature 90 Degrees F Net Weight 342 lb. Number of Doors 2 Doors Number of Drawers 2 Drawers Number of Shelves 1 Shelf Plug Type NEMA 5-15P Refrigerant Type R-290 Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 33-40 Degrees F	Hinge Location		
MaterialStainless SteelMaximum Ambient Temperature90 Degrees FNet Weight342 lb.Number of Doors2 DoorsNumber of Drawers2 DrawersNumber of Shelves1 ShelfPlug TypeNEMA 5-15PRefrigerant TypeR-290Starting Amps17.1 AmpsStarting Wattage1572 WattsStyleCounter HeightTemperature Range33 - 40 Degrees F	Horsepower	1/4 hp	
Maximum Ambient Temperature90 Degrees FNet Weight342 lb.Number of Doors2 DoorsNumber of Drawers2 DrawersNumber of Shelves1 ShelfPlug TypeNEMA 5-15PRefrigerant TypeR-290Starting Amps17.1 AmpsStarting Wattage1572 WattsStyleCounter HeightTemperature Range33 - 40 Degrees F	Insulation Material	Polyurethane Foam	
Net Weight342 lb.Number of Doors2 DoorsNumber of Drawers2 DrawersNumber of Shelves1 ShelfPlug TypeNEMA 5-15PRefrigerant TypeR-290Starting Amps17.1 AmpsStarting Wattage1572 WattsStyleCounter HeightTemperature Range33 - 40 Degrees F	Material	Stainless Steel	
Number of Doors2 DoorsNumber of Drawers2 DrawersNumber of Shelves1 ShelfPlug TypeNEMA 5-15PRefrigerant TypeR-290Starting Amps17.1 AmpsStarting Wattage1572 WattsStyleCounter HeightTemperature Range33 - 40 Degrees F	Maximum Ambient Temperature	90 Degrees F	
Number of Drawers Number of Shelves 1 Shelf Plug Type NEMA 5-15P Refrigerant Type R-290 Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 2 Drawers 1 Shelf NEMA 5-15P R-290 Counter Height 33 - 40 Degrees F	Net Weight	342 lb.	
Number of Shelves 1 Shelf Plug Type NEMA 5-15P Refrigerant Type R-290 Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 33 - 40 Degrees F	Number of Doors	2 Doors	
Plug TypeNEMA 5-15PRefrigerant TypeR-290Starting Amps17.1 AmpsStarting Wattage1572 WattsStyleCounter HeightTemperature Range33 - 40 Degrees F	Number of Drawers	2 Drawers	
Refrigerant Type R-290 Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 33 - 40 Degrees F	Number of Shelves	1 Shelf	
Starting Amps 17.1 Amps Starting Wattage 1572 Watts Style Counter Height Temperature Range 33 - 40 Degrees F	Plug Type	NEMA 5-15P	
Starting Wattage1572 WattsStyleCounter HeightTemperature Range33 - 40 Degrees F	Refrigerant Type	R-290	
StyleCounter HeightTemperature Range33 - 40 Degrees F	Starting Amps	17.1 Amps	
Temperature Range 33 - 40 Degrees F	Starting Wattage	1572 Watts	
	Style	Counter Height	
Top Capacity 353 lb.	Temperature Range	33 - 40 Degrees F	
	Top Capacity	353 lb.	



Plan View





Notes & Details

Make food preparation as convenient as possible with the Avantco 93" extra deep worktop refrigerator. With a spacious stainless steel worktop surface for slicing, dicing, assembling, mixing, and other food prep tasks, the unit features a 3 1/2" backsplash for wall protection and a refrigerated storage space below. The refrigerated portion is readily accessible through 4 drawers, 2 on each side, and 1 door in the middle. This door opens to an epoxy-coated steel shelf to help organize product. Drawers provide excellent organization for your food pans and can help maximize your kitchen's workflow. Drawers also allow you to quickly pull ingredients for faster operation and ease of use. Plus, 12 assorted divider bars are included, which fit in the drawers where they act as braces for full size or fractional pans. Easily reconfigure or remove the braces to best suit your inventory. Providing 25.4 cu. ft. of space in total, the refrigerator makes it easy to store fresh produce, condiments, and a range of other ingredients needed for the prep station.

This refrigerated unit is designed for outstanding durability to ensure that it withstands tough, busy kitchen environments with ease. It features a 430 type stainless steel exterior, which provides both strength and a smooth, sleek appearance. The interior, made with 304 type stainless steel, also offers the durability necessary for heavy, regular use.

This worktop refrigerator ensures optimal performance by operating with a 1/4 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. The foamed-in-place polyurethane insulation helps to trap in the cold air and to prevent the ambient air from entering. This ensures that all food held in the unit remains at food safe temperatures and ready for preparation or direct service to customers!

Operation of the refrigerator is easy, thanks to its special features. Monitor it by consulting the interior wall-mounted thermometer, and use the auto-defrost feature on the pre-programmed digital controller to maintain the refrigerator in tip-top shape. At the end of the day, take advantage of the casters and roll the unit aside to thoroughly clean the area. This worktop refrigerator requires a 115V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.