

ltem#:	1/8UBB3/8S		Project:	
O+. "		Data		Approvale

Avantco UBB-378-HC-S 79" Stainless Steel Counter Height Solid Door Back Bar Refrigerator with LED Lighting

Item #178UBB378S





Technical Data

Width	78 Inches
Depth	27 3/4 Inches
Height	36 1/4 Inches
Power Cord Length	96 Inches
Interior Width	66 3/8 Inches
Left Door Opening Width	20 1/4 Inches
Middle Door Opening Width	19 3/16 Inches
Packaging Width	80 11/16 Inches
Right Door Opening Width	20 1/4 Inches
Shelf Width	21 5/8 Inches

Features

- 1 1/2" thick stainless steel countertop with stainless steel interior exterior
- LED interior lighting
- Six adjustable epoxy-coated steel shelves can be removed to fit four 1/2 kegs
- Preprogrammed digital temperature controls with auto-defrost function for easy setup and maintenance
- 115V; 1/4 hp; R-290 refrigerant

Certifications



5-15P





ETL Sanitation



Technical Data

Double with Door Over	40.0/47 hashas
Depth with Door Open	48 9/16 Inches 21 7/8 Inches
Interior Depth	Standard
Nominal Depth Packaging Depth	30 5/16 Inches
Shelf Depth	21 1/4 Inches
Interior Height	30 1/2 Inches
Packaging Height	41 3/4 Inches
Amps	4.1 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	385 Watts
Access Type	Doors
BTU (LBP)	974 BTU
Capacity	(4) 1/2 Kegs 25.8 cu. ft.
Capacity (per Shelf)	88 lb.
Compressor Location	Side Mounted
Compressor Style	Side / Rear Breathing
Countertop Type	Stainless Steel
Door Style	Swing
Door Type	Solid
Exterior Finish	Stainless Steel
	Automatic Electric Defrost Digital Temperature Controller
Features	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets
Features Horsepower	Food Rated LED Lighting Locking Doors
	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets
Horsepower	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp
Horsepower Insulation Material	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam
Horsepower Insulation Material Material	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel
Horsepower Insulation Material Material Maximum Ambient Temperature	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb.
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz.
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 12.3 Amps
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps Starting Wattage	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 12.3 Amps 1155 Watts
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps Starting Wattage Style	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 12.3 Amps 1155 Watts 1/2 Barrel
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps Starting Wattage Style Temperature Range	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 12.3 Amps 1155 Watts 1/2 Barrel 33 - 41 Degrees F
Horsepower Insulation Material Material Maximum Ambient Temperature Net Weight Number of 12 oz. Bottles Number of 12 oz. Cans Number of Doors Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps Starting Wattage Style	Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets 1/4 hp Polyurethane Foam Stainless Steel 90 Degrees F 320 lb. 432 Bottles 384 Cans 3 Doors 4 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 12.3 Amps 1155 Watts 1/2 Barrel



Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-3-HC 79" stainless steel counter height solid door back bar refrigerator! Providing 23.4 cu. ft. of interior storage space, the unit comes with six shelves that accommodate up to 88 lb. each or (4) 1/2 kegs total. They're even illuminated by bright LED lighting for optimal product visibility. The epoxy-coated steel shelves are perfect for storing and organizing heavy bulk ingredients for your bar service, from bottles of ale to bottles of cider. Plus, since the unit is rated to safely store food products, it provides versatility and helps you maximize the space you have available.

The interior, made of strong 304 type stainless steel, is accessible through two solid doors. For overall durability, the unit's exterior is made with stainless steel and is topped with a type 304 stainless steel surface.

This back bar refrigerator ensures optimal performance by operating with a 1/4 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all products held in the unit remain at cool temperatures and are ready for immediate service to customers!

Delivering ease of use and maintenance, the refrigerator is easy to adjust with a digital temperature controller and features automatic defrost. Overall, the unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.