

ltem#:	1/8UBB3GHCS		Project:	
			· · ·	
Otv.		Date:		Annroyal.

Avantco UBB-3G-HC 69" Stainless Steel Counter Height Glass Door Back Bar Refrigerator with LED Lighting

Item#178UBB3GHCS







Technical Data

Width	69 1/8 Inches	
Depth	27 3/4 Inches	
Height	36 1/4 Inches	
Power Cord Length	106 Inches	
Interior Width	56 1/2 Inches	
Left Door Opening Width	21 1/2 Inches	
Packaging Width	71 1/2 Inches	
Right Door Opening Width	21 1/2 Inches	
Shelf Width	27 3/4 Inches	
Interior Depth	21 7/8 Inches	

Features

- 1 1/2" thick stainless steel countertop with stainless steel interior and exterior
- LED interior lighting
- Four adjustable epoxy-coated steel shelves can be removed to fit three 1/2 size
- Preprogrammed digital temperature controls featuring auto-defrost function for easy setup and mainte
- Uses R290 refrigerant; 3/7 hp; 115V

Certifications





ETL, US



ETL Sanitation




Technical Data

Nominal Depth	Standard	
Packaging Depth	30 1/2 Inches	
Shelf Depth	21 1/2 Inches	
Interior Height	30 1/2 Inches	
Packaging Height	41 3/4 Inches	
Amps	3.5 Amps	
Hertz	60 Hz	
Phase	1 Phase	
Voltage	115 Volts	
Wattage	325 Watts	
Access Type	Doors	
BTU (LBP)	974 BTU	
Capacity	(3) 1/2 Kegs 23.4 cu. ft.	
Capacity (per Shelf)	88 lb.	
Compressor Location	Side Mounted	
Countertop Type	Stainless Steel	
Door Style	Swing	
Door Type	Glass	
Exterior Finish	Stainless Steel	
Features	Automatic Electric Defrost Digital Temperature Controller Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets	
Horsepower	3/7 hp	
Insulation Material	Polyurethane Foam	
Material	Stainless Steel	
Maximum Ambient Temperature	90 Degrees F	
Net Weight	302 lb.	
Number of 12 oz. Bottles	352 Bottles	
Number of 12 oz. Cans	320 Cans	
Number of Doors	2 Doors	
Number of Kegs	3 Kegs	
Number of Shelves	4 Shelves	
Plug Type	NEMA 5-15P	
Refrigerant Capacity	2.5 oz.	
Refrigerant Type	R-290	
Shelf Material	Epoxy-Coated Steel	
Starting Amps	10.5 Amps	
Starting Wattage	975 Watts	
Temperature Range	33 - 40 Degrees F	
Top Capacity	353 lb.	
Тор Туре	Counter Height	



Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-48G-HC-S 48" counter height narrow back bar refrigerator! Providing 13 cu. ft. of interior storage space, the unit fits up to (2) 1/2 kegs and houses four shelves that each accommodate up to 88 lb. They're even illuminated by bright LED lighting for optimal product visibility. The epoxy-coated steel shelves are perfect for storing and organizing heavy bulk ingredients for your bar service, from bottles of ale to bottles of cider. Plus, with a narrow depth design, the unit fits in spaces other units can't, helping you to maximize the space you have available.

The interior, made of strong 304 type stainless steel, is accessible through two glass doors. Because they're made of glass, the doors provide excellent product visibility, enabling you to easily view your current drink or ingredient selection for efficient drink preparation. For overall durability, the unit's exterior is made with sleek stainless steel and is topped with a type 304 stainless steel surface.

This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all beverages held in the unit remain at cool temperatures and are ready for immediate service to customers! The unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

MARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.