

ltem#:	1/8UBB48GTGS		Project: _		
O+1.11		Data		Approvale	

Avantco UBB-48-GT-G-S 48" Stainless Steel Underbar Height Narrow Glass Door Back Bar Refrigerator with Galvanized Top and LED Lighting

Item #178UBB48GTGS







Technical Data

Width	48 3/4 Inches		
Depth	24 7/16 Inches		
Height	34 13/16 Inches		
Power Cord Length	106 Inches		
Interior Width	36 1/4 Inches		
Left Door Opening Width	16 7/16 Inches		
Packaging Width	51 1/4 Inches		
Right Door Opening Width	16 7/16 Inches		
Shelf Width	17 5/8 Inches		
Interior Depth	18 1/2 Inches		

Features

- Galvanized steel top with stainless steel interior and stainless steel exterior
- LED interior lighting
- Four adjustable epoxy-coated steel shelves can be removed to fit two 1/2 kegs
- Glass door and bright, LED lighting ensure easy product visibility and retrieval
- 115V; 3/7 hp; R290 refrigerant

Certifications



5-15P





ETL Sanitation




Technical Data

Nominal Depth	Narrow		
Packaging Depth	27 1/2 Inches		
Shelf Depth	18 1/8 Inches		
Interior Height	29 Inches		
Packaging Height	41 3/4 Inches		
Amps	3.5 Amps		
Hertz	60 Hz		
Phase	1 Phase		
Voltage	115 Volts		
Wattage	325 Watts		
Access Type	Doors		
BTU (LBP)	974 BTU		
Capacity	(2) 1/2 Kegs 13 cu. ft.		
Capacity (per Shelf)	88 lb.		
Compressor Location	Side Mounted		
Countertop Type	Galvanized Steel		
Door Style	Swing		
Door Type	Glass		
Exterior Finish	Stainless Steel		
Features	Automatic Electric Defrost Digital Temperature Controller Food Rated LED Lighting Locking Doors Removable Magnetic Door Gaskets		
Horsepower	3/7 hp		
Insulation Material	Polyurethane Foam		
Material	Stainless Steel		
Maximum Ambient Temperature	90 Degrees F		
Net Weight	231 lb.		
Number of 12 oz. Bottles	196 Bottles		
Number of 12 oz. Cans	144 Cans		
Number of Doors	2 Doors		
Number of Kegs	2 Kegs		
Number of Shelves	4 Shelves		
Plug Type	NEMA 5-15P		
Refrigerant Capacity	2.5 oz.		
Refrigerant Type	R-290		
Shelf Material	Epoxy-Coated Steel		
Starting Amps	10.5 Amps		
Starting Wattage	975 Watts		
Temperature Range	33 - 40 Degrees F		
Top Capacity	353 lb.		
Тор Туре	Below Counter		



Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-48-HC-S 48" counter height narrow back bar refrigerator! Providing 13 cu. ft. of interior storage space, the unit fits up to (2) 1/2 kegs and houses four shelves that each accommodate up to 88 lb. They're even illuminated by bright LED lighting for optimal product visibility. The epoxy-coated steel shelves are perfect for storing and organizing heavy bulk ingredients for your bar service, from bottles of ale to bottles of cider. Plus, with a narrow depth design, the unit fits in spaces other units can't, helping you to maximize the space you have available.

The interior, made of strong 201 type stainless steel, is accessible through two solid doors. For overall durability, the unit's exterior is made with sleek stainless steel and is topped with a type 304 stainless steel surface. This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all beverages held in the unit remain at cool temperatures and are ready for immediate service to customers! The unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling. For long-lasting quality assurance and peace of mind, this unit also comes with a 2 year Parts and Labor Warranty.

MARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.