

ltem#:	178UBB72HC		Project:		
O+v.		Date		Approval:	

Avantco UBB-72-HC 73" Black Counter Height Narrow Solid Door Back Bar Refrigerator with LED Lighting

Item#178UBB72HC







Technical Data

Width	72 3/4 Inches		
Depth	24 7/16 Inches		
Height	36 1/4 Inches		
Power Cord Length	106 Inches		
Interior Width	60 1/8 Inches		
Left Door Opening Width	17 13/16 Inches		
Middle Door Opening Width	17 13/16 Inches		
Packaging Width	75 1/4 Inches		
Right Door Opening Width	17 13/16 Inches		
Shelf Width	19 - 20 1/2 Inches		

Features

- 1 1/2" thick stainless steel countertop with stainless steel interior and black coated steel exterio
- LED interior lighting
- Six adjustable epoxy-coated steel shelves can be removed to fit three 1/2 kegs
- Preprogrammed digital temperature controls featuring auto-defrost function for easy setup and mainte
- 115V; 3/7 hp; R290 refrigerant

Certifications



ETL, US



(II)

ETL Sanitation




Technical Data

Interior Depth	18 1/2 Inches
Nominal Depth	Narrow
Packaging Depth	27 1/2 Inches
Shelf Depth	19 - 20 1/2 Inches
Interior Height	30 1/2 Inches
Packaging Height	41 3/4 Inches
Amps	3.5 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	325 Watts
Access Type	Doors
BTU (LBP)	974 BTU
Capacity	(3) 1/2 Kegs 21.6 cu. ft.
Capacity (per Shelf)	88 lb.
Casters	Without Casters
Compressor Location	Side Mounted
Countertop Type	Stainless Steel
Door Style	Swing
Door Type	Solid
Exterior Finish	Black
Features	Automatic Electric Defrost Digital Temperature Controller Food Rated LED Lighting Removable Magnetic Door Gaskets
Horsepower	3/7 hp
Insulation Material	Polyurethane Foam
Material	Black Coated Steel / Stainless Steel
Maximum Ambient Temperature	90 Degrees F
Net Weight	331 lb.
Number of 12 oz. Bottles	308 Bottles
Number of 12 oz. Cans	
	252 Cans
Number of Doors	252 Cans 3 Doors
Number of Doors Number of Kegs	
	3 Doors
Number of Kegs	3 Doors 3 Kegs 6 Shelves NEMA 5-15P
Number of Kegs Number of Shelves	3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz.
Number of Kegs Number of Shelves Plug Type	3 Doors 3 Kegs 6 Shelves NEMA 5-15P
Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material	3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz.
Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type	3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 10.5 Amps
Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material	3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel
Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps Starting Wattage Temperature Range	3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 10.5 Amps 975 Watts 33 - 40 Degrees F
Number of Kegs Number of Shelves Plug Type Refrigerant Capacity Refrigerant Type Shelf Material Starting Amps Starting Wattage	3 Doors 3 Kegs 6 Shelves NEMA 5-15P 2.5 oz. R-290 Epoxy-Coated Steel 10.5 Amps 975 Watts



Plan View



Notes & Details

Optimize the space behind your bar by adding refrigerated storage with this Avantco UBB-72-HC 73" counter height narrow back bar refrigerator! Providing 21.6 cu. ft. of interior storage space, the unit fits up to (3) 1/2 kegs and houses 6 shelves that each accommodate up to 88 lb. The epoxy-coated steel shelves are perfect for storing and organizing beverages for your bar service, from bottles of ale and beer to cans of crisp ciders. Plus, with a narrow design, the unit fits in spaces other units can't, helping you to maximize the space you have available.

The interior, made of strong 304 type stainless steel, is accessible through three solid doors. For overall durability, the unit's exterior is made with black coated steel and is topped with a type 304 stainless steel surface.

This back bar refrigerator ensures optimal performance by operating with a 3/7 hp refrigeration system that circulates R290 hydrocarbon refrigerant to maintain temperatures from 33 to 40 degrees Fahrenheit. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. The foamed-in-place polyurethane insulation provides the refrigerator with additional structural integrity and ensures that all beverages held in the unit remain at cool temperatures and are ready for immediate service to customers! The unit requires a 115V electrical connection for operation and even comes with adjustable feet for simple, convenient leveling.

MARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.