

Item #: 178UDD1HCS Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco UDD-1-HC-S Single Tap Kegerator Beer Dispenser - Stainless Steel, (1) 1/2 Keg Capacity

Item #178UDD1HCS



Technical Data

Width	23 1/2 Inches
Depth	30 1/4 Inches
Height	39 3/4 Inches
Power Cord Length	108 Inches
Interior Width	19 1/2 Inches
Left Door Opening Width	19 11/16 Inches
Packaging Width	26 Inches
Interior Depth	18 1/8 Inches
Nominal Depth	Standard
Packaging Depth	32 1/4 Inches

Features

- Holds (1) 1/2 keg
- 1 tap tower with a 10 1/4" faucet height
- Digital controls for easy-to-read temperature display
- Includes (1) "D" system keg coupler
- 115V; 1/4 hp compressor uses R290 hydrocarbon refrigerant

Certifications



5-15P



ETL, US




ETL Sanitation

Technical Data

Faucet Height	10 1/4 Inches
Interior Height	28 5/8 Inches
Overall Height	55 3/4 Inches
Packaging Height	45 Inches
Tap Tower Height	16 Inches
Tap Tower Diameter	3 Inches
Amps	1.92 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts
Wattage	216 Watts
BTU (LBP)	666 BTU
Capacity	(1) 1/2 Kegs
Casters	With Casters
Compressor Location	Rear Mounted
Door Type	Solid
Exterior Finish	Stainless Steel
Features	Automatic Electric Defrost Digital Temperature Controller Removable Magnetic Door Gaskets
Horsepower	1/4 hp
Insulation Material	Polyurethane Foam
Material	Stainless Steel
Net Volume	7 4/5 cu. ft.
Net Weight	132 lb.
Number of Doors	1 Doors
Number of Kegs	1 Keg
Number of Shelves	0/0 Shelves
Number of Taps	1 Tap
Plug Type	NEMA 5-15P
Refrigerant Capacity	2.1 oz.
Refrigerant Type	R-290
Starting Amps	5.76 Amps
Starting Wattage	648 Watts
Style	1/2 Barrel
Temperature Range	33 - 40 Degrees F
Top Capacity	176 lb.
Type	Kegeators / Beer Dispensers

Plan View



Notes & Details

Whether you operate a pub, banquet hall, catering service, or facilitate other special events, this Avantco UDD-1-HC-S triple tap beer dispenser is an excellent way to offer crisp, refreshing draft beer to your guests without investing in a complex built-in tap system! This unit features a triple tap tower with a 10 1/4" faucet height that allows you to easily fill pint glasses and pitchers with local microbrews, international macrobrews, and everything in between. It holds (1) 1/2 keg, (2) 1/4 kegs, or (4) 1/6 barrel kegs, and features 1 solid door that will not only self-close to prevent potential energy loss, but also lock to prevent theft during off hours. This unit is equipped with knockout plugs to install external CO2 lines.

Unlike many competitive beer dispensers, this model ships with a coupler so that you can tap kegs right out of the box! This commercial kegerator features a sleek stainless steel finish and a 1 1/2" thick stainless steel top that is both durable and extremely simple to clean, while a built-in drip tray further expedites end-of-day cleaning. It has a 1/4 hp refrigeration system that circulates R290 hydrocarbon refrigerant. R290 refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3, making it an energy-efficient choice for your business. A 115V electrical connection is required for operation.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.